



NSAI
Standards

Irish Standard
I.S. EN ISO 16827:2014

Non-destructive testing - Ultrasonic testing - Characterization and sizing of discontinuities (ISO 16827:2012)

I.S. EN ISO 16827:2014

Incorporating amendments/corrigenda/National Annexes issued since publication:

The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:

I.S. xxx: Irish Standard — national specification based on the consensus of an expert panel and subject to public consultation.

S.R. xxx: Standard Recommendation — recommendation based on the consensus of an expert panel and subject to public consultation.

SWiFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.

This document replaces/revises/consolidates the NSAI adoption of the document(s) indicated on the CEN/CENELEC cover/Foreword and the following National document(s):

NOTE: The date of any NSAI previous adoption may not match the date of its original CEN/CENELEC document.

This document is based on:

EN ISO 16827:2014

Published:

2014-03-05

This document was published under the authority of the NSAI and comes into effect on:

2014-03-15

ICS number:

19.100

NOTE: If blank see CEN/CENELEC cover page

NSAI
1 Swift Square,
Northwood, Santry
Dublin 9

T +353 1 807 3800
F +353 1 807 3838
E standards@nsai.ie
W NSAI.ie

Sales:
T +353 1 857 6730
F +353 1 857 6729
W standards.ie

Údarás um Chaighdeáin Náisiúnta na hÉireann

EUROPEAN STANDARD

EN ISO 16827

NORME EUROPÉENNE

EUROPÄISCHE NORM

March 2014

ICS 19.100

Supersedes EN 583-5:2000

English Version

Non-destructive testing - Ultrasonic testing - Characterization and sizing of discontinuities (ISO 16827:2012)

Essais non destructifs - Contrôle par ultrasons -
Caractérisation et dimensionnement des discontinuités (ISO
16827:2012)

Zerstörungsfreie Prüfung - Ultraschallprüfung -
Beschreibung und Größenbestimmung von
Inhomogenitäten (ISO 16827:2012)

This European Standard was approved by CEN on 9 February 2014.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

Foreword.....	3
----------------------	----------

Foreword

The text of ISO 16827:2012 has been prepared by Technical Committee ISO/TC 135 “Non-destructive testing” of the International Organization for Standardization (ISO) and has been taken over as EN ISO 16827:2014 by Technical Committee CEN/TC 138 “Non-destructive testing” the secretariat of which is held by AFNOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by September 2014, and conflicting national standards shall be withdrawn at the latest by September 2014.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 583-5:2000.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Endorsement notice

The text of ISO 16827:2012 has been approved by CEN as EN ISO 16827:2014 without any modification.

This page is intentionally left blank

INTERNATIONAL STANDARD

ISO
16827

First edition
2012-04-01

Non-destructive testing — Ultrasonic testing — Characterization and sizing of discontinuities

*Essais non destructifs — Contrôle par ultrasons — Caractérisation et
dimensionnement des discontinuités*



Reference number
ISO 16827:2012(E)

© ISO 2012



COPYRIGHT PROTECTED DOCUMENT

© ISO 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	v
Introduction.....	vi
1 Scope	1
2 Normative references	1
3 Principles of characterization of discontinuities	1
3.1 General	1
3.2 Requirements for surface condition.....	2
4 Pulse echo techniques.....	2
4.1 General	2
4.2 Location of discontinuity.....	2
4.3 Orientation of discontinuity.....	2
4.4 Assessment of multiple indications	3
4.5 Shape of discontinuity	3
4.5.1 Simple classification	3
4.5.2 Detailed classification of shape	4
4.6 Maximum echo height of indication	4
4.7 Size of discontinuity.....	4
4.7.1 General	4
4.7.2 Maximum echo height techniques.....	4
4.7.3 Probe movement sizing techniques	5
4.7.4 Selection of sizing techniques	5
4.7.5 Sizing techniques with focussing ultrasonic probes	6
4.7.6 Use of mathematical algorithms for sizing	6
4.7.7 Special sizing techniques	6
5 Transmission technique	7
5.1 General	7
5.2 Location of discontinuity.....	7
5.3 Evaluation of multiple discontinuities.....	7
5.4 Reduction of signal amplitude	8
5.5 Sizing of discontinuity	8
Annex A (normative) Analysis of multiple indications	12
A.1 Lateral characterisation	12
A.2 Transverse (Through-thickness) characterisation	12
A.3 Shadow technique.....	12
Annex B (normative) Techniques for the classification of discontinuity shape	14
B.1 Simple classification	14
B.1.1 General	14
B.1.2 Reconstruction technique	14
B.1.3 Echo envelope technique	14
B.2 Detailed classification.....	14
B.2.1 General	14
B.2.2 Echodynamic pattern technique.....	15
B.2.3 Directional reflectivity	17
B.3 Combination of data.....	17
Annex C (informative) Maximum echo height sizing technique.....	25
C.1 Distance-gain-size (DGS) technique.....	25
C.1.1 Principle.....	25
C.1.2 Applications and limitations.....	25
C.2 Distance-amplitude-correction (DAC) curve technique	25
C.2.1 Principle.....	25

ISO 16827:2012(E)

C.2.2	Applications and limitations	26
Annex D	(normative) Probe movement sizing techniques	27
D.1	Fixed amplitude level techniques	27
D.1.1	Principle	27
D.1.2	Application and limitations	27
D.2	6 dB drop from maximum technique	27
D.2.1	Principle	27
D.2.2	Application and limitations	27
D.3	12 dB or 20 dB drop from maximum technique	28
D.3.1	Principle	28
D.3.2	Application and limitations	28
D.4	Drop to noise level technique	28
D.4.1	Principle	28
D.4.2	Application and limitations	28
D.5	6 dB drop tip location technique	29
D.5.1	Principle	29
D.5.2	Application and limitations	29
D.6	Beam axis tip location technique	29
D.6.1	Principle	29
D.6.2	Application and limitations	29
D.7	20 dB drop tip location technique	30
D.7.1	Principle	30
D.7.2	Application and limitations	30
Annex E	(normative) Iterative sizing technique	39
E.1	Scope	39
E.2	Normal incidence testing	39
E.2.1	Principle	39
E.2.2	Adjustment of gain	39
E.2.3	Procedure	39
E.3	Oblique incidence testing	40
Annex F	(normative) Mathematical algorithms for the estimation of the actual size of a discontinuity	45
F.1	Large planar discontinuities	45
F.2	Small planar discontinuities	46
F.3	Planar discontinuities in a cylindrical test object	48
Annex G	(informative) Examples of special sizing techniques	50
G.1	Tip diffraction techniques	50
G.2	Synthetic aperture focussing technique (SAFT)	51

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 16827 was prepared by Technical Committee ISO/TC 135, *Non-destructive testing*, Subcommittee SC 3, *Ultrasonic testing*.

ISO 16827:2012(E)

Introduction

This International Standard is based on EN 583-5:2000+A1:2003, *Non-destructive testing — Ultrasonic examination — Part 5: Characterization and sizing of discontinuities*.

The following International Standards are linked.

ISO 16810, *Non-destructive testing — Ultrasonic testing — General principles*

ISO 16811, *Non-destructive testing — Ultrasonic testing — Sensitivity and range setting*

ISO 16823, *Non-destructive testing — Ultrasonic testing — Transmission technique*

ISO 16826, *Non-destructive testing — Ultrasonic testing — Examination for discontinuities perpendicular to the surface*

ISO 16827, *Non-destructive testing — Ultrasonic testing — Characterization and sizing of discontinuities*

ISO 16828, *Non-destructive testing — Ultrasonic testing — Time-of-flight diffraction technique as a method for detection and sizing of discontinuities*

Non-destructive testing — Ultrasonic testing — Characterization and sizing of discontinuities

1 Scope

This document specifies the general principles and techniques for the characterization and sizing of previously detected discontinuities in order to ensure their evaluation against applicable acceptance criteria. It is applicable, in general terms, to discontinuities in those materials and applications covered by ISO 16810.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 16810:2012, *Non-destructive testing — Ultrasonic testing — General principles*

ISO 16811, *Non-destructive testing — Ultrasonic testing — Sensitivity and range setting*

ISO 16823, *Non-destructive testing — Ultrasonic testing — Transmission technique*

ISO 16828, *Non-destructive testing — Ultrasonic testing — Time-of-flight diffraction technique as a method for detection and sizing of discontinuities*

ISO 23279, *Non-destructive testing of welds — Ultrasonic testing — Characterization of indications in welds*

3 Principles of characterization of discontinuities

3.1 General

Characterization of a discontinuity involves the determination of those features which are necessary for its evaluation with respect to known acceptance criteria.

Characterization of a discontinuity may include:

- a) determination of basic ultrasonic parameters (echo height, time of flight);
- b) determination of its basic shape and orientation;
- c) sizing, which may take the form of either:
 - i) the measurement of one or more dimensions (or area/volume), within the limitations of the methods; or
 - ii) the measurement of some agreed parameter e.g. echo height, where this is taken as representative of its physical size;
- d) location e.g. the proximity to the surface or to other discontinuities;
- e) determination of any other parameters or characteristics that may be necessary for complete evaluation;

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

-
- [Looking for additional Standards? Visit Intertek Inform Infostore](#)
 - [Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation](#)
-