



NSAI
Standards

Irish Standard
I.S. EN ISO 13788:2012

Hygrothermal performance of building components and building elements - Internal surface temperature to avoid critical surface humidity and interstitial condensation - Calculation methods (ISO 13788:2012)

I.S. EN ISO 13788:2012

Incorporating amendments/corrigenda/National Annexes issued since publication:

The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:

I.S. xxx: Irish Standard – national specification based on the consensus of an expert panel and subject to public consultation.

S.R. xxx: Standard Recommendation - recommendation based on the consensus of an expert panel and subject to public consultation.

SWIFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.

This document replaces:
EN ISO 13788:2001

This document is based on: EN ISO 13788:2012
Published: 3 December, 2013

This document was published under the authority of the NSAI and comes into effect on:
3 December, 2013

ICS number:

91.060.01
91.120.10

NSAI
1 Swift Square,
Northwood, Santry
Dublin 9

T +353 1 807 3800
F +353 1 807 3838
E standards@nsai.ie
W NSAI.ie

Sales:
T +353 1 857 6730
F +353 1 857 6729
W standards.ie

Údarás um Chaighdeáin Náisiúnta na hÉireann

English Version

Hygrothermal performance of building components and building elements - Internal surface temperature to avoid critical surface humidity and interstitial condensation - Calculation methods (ISO 13788:2012)

Performance hygrothermique des composants et parois de bâtiments - Température superficielle intérieure permettant d'éviter l'humidité superficielle critique et la condensation dans la masse - Méthodes de calcul (ISO 13788:2012)

Wärme- und feuchtetechnisches Verhalten von Bauteilen und Bauelementen - Raumseitige Oberflächentemperatur zur Vermeidung kritischer Oberflächenfeuchte und Tauwasserbildung im Bauteilinneren - Berechnungsverfahren (ISO 13788:2012)

This European Standard was approved by CEN on 28 December 2012.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

Page

Foreword.....3

Foreword

This document (EN ISO 13788:2012) has been prepared by Technical Committee ISO/TC 163 "Thermal performance and energy use in the built environment" in collaboration with Technical Committee CEN/TC 89 "Thermal performance of buildings and building components" the secretariat of which is held by SIS.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by June 2013, and conflicting national standards shall be withdrawn at the latest by June 2013.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN ISO 13788:2001.

According to the CEN/CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Endorsement notice

The text of ISO 13788:2012 has been approved by CEN as a EN ISO 13788:2012 without any modification.

This page is intentionally left BLANK.

I.S. EN ISO 13788:2012
INTERNATIONAL
STANDARD

ISO
13788

Second edition
2012-12-15

**Hygrothermal performance of
building components and building
elements — Internal surface
temperature to avoid critical
surface humidity and interstitial
condensation — Calculation methods**

*Performance hygrothermique des composants et parois de
bâtiments — Température superficielle intérieure permettant d'éviter
l'humidité superficielle critique et la condensation dans la masse —
Méthodes de calcul*



Reference number
ISO 13788:2012(E)

© ISO 2012



COPYRIGHT PROTECTED DOCUMENT

© ISO 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions, symbols and units	1
3.1 Terms and definitions.....	1
3.2 Symbols and units.....	3
3.3 Subscripts.....	4
4 Input data for the calculations	4
4.1 Material and product properties.....	4
4.2 External boundary conditions.....	4
4.3 Internal boundary conditions.....	6
4.4 Surface resistances.....	6
5 Calculation of surface temperature to avoid critical surface humidity	7
5.1 General.....	7
5.2 Determining parameters.....	7
5.3 Design for avoidance of mould growth, corrosion or other moisture damage.....	7
5.4 Design for the limitation of surface condensation on low thermal inertia elements.....	8
6 Calculation of interstitial condensation	9
6.1 General.....	9
6.2 Principle.....	9
6.3 Limitation of sources of error.....	10
6.4 Calculation.....	10
6.5 Criteria used to assess building components.....	16
7 Calculation of drying of building components	16
7.1 General.....	16
7.2 Principle.....	17
7.3 Specification of the method.....	17
7.4 Criteria used to assess drying potential of building components.....	17
Annex A (informative) Internal boundary conditions	18
Annex B (informative) Examples of calculation of the temperature factor at the internal surface to avoid critical surface humidity	20
Annex C (informative) Examples of calculation of interstitial condensation	24
Annex D (informative) Example of the calculation of the drying of a wetted layer	34
Annex E (informative) Relationships governing moisture transfer and water vapour pressure	37
Bibliography	40

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 13788 was prepared by Technical Committee ISO/TC 163, *Thermal performance and energy use in the built environment*, Subcommittee SC 2, *Calculation methods* in cooperation with CEN/TC 89, *Thermal performance of buildings and building components*.

This second edition cancels and replaces the first edition (ISO 13788:2001), which has been technically revised.

Introduction

Moisture transfer is a very complex process and the knowledge of moisture transfer mechanisms, material properties, initial conditions and boundary conditions is often limited. Therefore this International Standard lays down simplified calculation methods, which assume that moisture transport is by vapour diffusion alone and use monthly climate data. The standardization of these calculation methods does not exclude use of more advanced methods. If other sources of moisture, such as rain penetration or convection, are negligible, the calculations will normally lead to designs well on the safe side and if a construction fails a specified design criterion according to this procedure, more accurate methods may be used to show that the design will pass.

This International Standard deals with:

- a) the critical surface humidity likely to lead to problems such as mould growth on the internal surfaces of buildings,
- b) interstitial condensation within a building component, in:
 - heating periods, where the internal temperature is usually higher than outside;
 - cooling periods, where the internal temperature is usually lower than the outside;
 - cold stores, where the internal temperature is always lower than outside.
- c) an estimate of the time taken for a component, between high vapour resistance layers, to dry, after wetting from any source, and the risk of interstitial condensation occurring elsewhere in the component during the drying process.

This International Standard does not cover other aspects of moisture, e.g. ground water and ingress of precipitation.

In some cases, airflow from the interior of the building into the structure is the major mechanism for moisture transport, which can increase the risk of condensation problems very significantly. This International Standard does not address this issue; where it is felt to be important, more advanced assessment methods should be considered.

The limitations on the physical processes covered by this International Standard mean that it can provide a more robust analysis of some structures than others. The results will be more reliable for lightweight, airtight structures that do not contain materials that store large amounts of water. They will be less reliable for structures with large thermal and moisture capacity and which are subject to significant air leakage.

Hygrothermal performance of building components and building elements — Internal surface temperature to avoid critical surface humidity and interstitial condensation — Calculation methods

1 Scope

This International Standard gives simplified calculation methods for:

- a) The internal surface temperature of a building component or building element below which mould growth is likely, given the internal temperature and relative humidity. The method can also be used to assess the risk of other internal surface condensation problems.
- b) The assessment of the risk of interstitial condensation due to water vapour diffusion. The method used does not take account of a number of important physical phenomena including:
 - the variation of material properties with moisture content;
 - capillary suction and liquid moisture transfer within materials;
 - air movement from within the building into the component through gaps or within air spaces;
 - the hygroscopic moisture capacity of materials.

Consequently, the method is applicable only where the effects of these phenomena can be considered to be negligible.

- c) The time taken for water, from any source, in a layer between two high vapour resistance layers to dry out and the risk of interstitial condensation occurring elsewhere in the component during the drying process.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 6946:2007, *Building components and building elements — Thermal resistance and thermal transmittance — Calculation method*

ISO 9346, *Hygrothermal performance of buildings and building materials — Physical quantities for mass transfer — Vocabulary*

ISO 15927-1, *Hygrothermal performance of buildings — Calculation and presentation of climatic data — Part 1: Monthly means of single meteorological elements*

3 Terms and definitions, symbols and units

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 9346 and the following apply.

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

-
- [Looking for additional Standards? Visit Intertek Inform Infostore](#)
 - [Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation](#)
-