

Irish Standard I.S. EN 4078:2009

Aerospace series - Inserts, threaded, thin wall, locked and self-locking, in heat resisting steel, MoS2 lubricated -Classification: 1 100 MPa (at ambient temperature) / 315°C

© NSAI 2009 No copying without NSAI permission except as permitted by copyright law.

Incorporating amendments/corrigenda issued since publication:

This document replaces:	<i>This document is based on:</i> EN 4078:2009	Publish 11 Nov	<i>hed:</i> vember, 2009	
This document was published under the authority of the NSAI and comes into effect on: 27 November, 2009			ICS number: 49.030.30	
NSAI 1 Swift Square, T +3 Northwood, Santry F +3 Dublin 9 E st W N	Sales: 353 1 807 3800 T +353 1 857 6730 353 1 807 3838 F +353 1 857 6729 tandards@nsai.ie W standards.ie NSAI.ie			
Údarás um Chaighdeáin Náisiúnta na hÉireann				

EUROPEAN STANDARD

EN 4078

EUROPÄISCHE NORM

November 2009

ICS 49.030.30

English Version

Aerospace series - Inserts, threaded, thin wall, locked and selflocking, in heat resisting steel, MoS2 lubricated - Classification: 1 100 MPa (at ambient temperature) / 315 °C

Série aérospatiale - Douilles filetées, à paroi mince, freinées et à freinage interne, en acier résistant à chaud lubrifiées MoS2 - Classification: 1 100 MPa (à température ambiante) / 315 °C Luft- und Raumfahrt - Gewindeeinsatz, dünnwandig, gesichert und schraubensichernd, aus hochwarmfestem Stahl, MoS2 geschmiert - Klasse: 1 100 MPa (bei Raumtemperatur) / 315 °C

This European Standard was approved by CEN on 15 September 2009.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

© 2009 CEN All rights of exploitation in any form and by any means reserved worldwide for CEN national Members.

Ref. No. EN 4078:2009: E

EN 4078:2009 (E)

Contents

Page

Forev	vord	3
1	Scope	4
2	Normative references	4
2.1	Configuration – Dimensions – Masses	4
2.2	Materials	4
2.3	Surface treatment	4
3	Designation	7
4	Marking	7
5	Installation	7
6	Technical specification	7

Foreword

This document (EN 4078:2009) has been prepared by the Aerospace and Defence Industries Association of Europe - Standardization (ASD-STAN).

After enquiries and votes carried out in accordance with the rules of this Association, this Standard has received the approval of the National Associations and the Official Services of the member countries of ASD, prior to its presentation to CEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by May 2010, and conflicting national standards shall be withdrawn at the latest by May 2010.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

1 Scope

This European Standard specifies the characteristics of threaded thin wall inserts, locked and with a self-locking feature achieved by deforming out-of-round the internal thread of mid length, in heat resisting steel, MoS_2 lubricated.

Classification : 1 100 MPa¹⁾ / 315 °C²⁾.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 2424, Aerospace series - Marking of aerospace products

EN 2491, Aerospace series — Molybdenum disulphide dry lubricants — Coating methods

EN 4217, Aerospace series — Inserts, thin wall, for airframe applications — Installation and removal procedure³⁾

EN 4218, Aerospace series — Inserts, thin wall, self-locking, MJ threads, in heat resisting steel, MoS_2 lubricated — Classification 1 100 MPa (at ambient temperature) / 315 °C — Technical specification³)

ISO 965-1, ISO general-purpose metric screw threads — Tolerances — Part 1: Principles and basic data

ISO 5855-2, Aerospace — MJ threads — Part 2: Limit dimensions for bolts and nuts

TR 3791, Aerospace series — Materials for self-locking nuts, threaded inserts and screw thread inserts of temperature classes \geq 425 °C

2.1 Configuration – Dimensions – Masses

See Figure 1 and Table 1.

Dimensions and tolerances are expressed in millimetres and apply before MoS₂ lubrication.

Details of form not stated are at the manufacturer's option.

2.2 Materials

TR 3791.

2.3 Surface treatment

EN 2491, thickness not specified.

¹⁾ Corresponds to the minimum tensile stress which the insert is able to withstand at ambient temperature without breaking or cracking when tested with a bolt of a higher strength class.

²⁾ Maximum temperature that the insert is able to withstand, without permanent alteration to its original characteristics, after ambient temperature has been restored. The maximum temperature is conditioned by the MoS_2 lubricant.

³⁾ In preparation at the date of publication of this standard.



This is a free preview. Purchase the entire publication at the link below:

Product Page

S Looking for additional Standards? Visit Intertek Inform Infostore

> Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation