This is a free page sample. Access the full version online.



Irish Standard I.S. EN 61158-4-18:2012

Industrial communication networks -Fieldbus specifications -- Part 4-18: Data-link layer protocol specification -Type 18 elements (IEC 61158-4-18:2010 (EQV))

 $\ensuremath{\mathbb{C}}$ NSAI 2012 No copying without NSAI permission except as permitted by copyright law.

Incorporating amendments/corrigenda issued since publication:

The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:

I.S. xxx: Irish Standard – national specification based on the consensus of an expert panel and subject to public consultation.

S.R. xxx: Standard Recommendation - recommendation based on the consensus of an expert panel and subject to public consultation.

SWIFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.

<i>This document replaces:</i> EN 61158-4-18:2008	EN 61158-4-18:20	<i>This document is based on:</i> EN 61158-4-18:2012 EN 61158-4-18:2008		<i>Published:</i> 25 May, 2012 29 February, 2008	
This document was published under the authority of the NSAI ar 1 June, 2012	id comes into effect on:			ICS number: 25.040.40 35.100.20 35.110	
1 Swift Square, F + Northwood, Santry E s Dublin 9	1 Swift Square, F +353 1 807 3838 T +353 1 857 6730 Northwood, Santry E standards@nsai.ie F +353 1 857 6729				
Údarás um Ch	aighdeáin Náisiún	ta na hÉireai	าท		

EUROPEAN STANDARD

EN 61158-4-18

NORME EUROPÉENNE EUROPÄISCHE NORM

May 2012

ICS 25.040.40; 35.100.20; 35.110

Supersedes EN 61158-4-18:2008

English version

Industrial communication networks -Fieldbus specifications -Part 4-18: Data-link layer protocol specification -Type 18 elements

(IEC 61158-4-18:2010)

Réseaux de communication industriels -Spécifications de bus de terrain -Partie 4-18: Spécification du protocole de couche de liaison de données -Eléments de type 18 (CEI 61158-4-18:2010) Industrielle Kommunikationsnetze -Feldbusse -Teil 4-18: Protokollspezifikation des Data Link Layer (Sicherungsschicht) -Typ 18-Elemente (IEC 61158-4-18:2010)

This European Standard was approved by CENELEC on 2012-03-28. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

Management Centre: Avenue Marnix 17, B - 1000 Brussels

© 2012 CENELEC - All rights of exploitation in any form and by any means reserved worldwide for CENELEC members.

EN 61158-4-18:2012

- 2 -

Foreword

The text of document 65C/605/FDIS, future edition 2 of IEC 61158-4-18, prepared by SC 65C, "Industrial networks", of IEC/TC 65, "Industrial-process measurement, control and automation" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 61158-4-18:2012.

The following dates are fixed:

•	latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement	(dop)	2012-12-28
•	latest date by which the national standards conflicting with the	(dow)	2015-03-28

This document supersedes EN 61158-4-18:2008.

document have to be withdrawn

EN 61158-4-18:2012 includes the following significant technical changes with respect to EN 61158-4-18:2008:

- Editorial improvements;
- Addition of cyclic data segmenting.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 61158-4-18:2010 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC/TR 61158-1:2010	NOTE	Harmonized as CLC/TR 61158-1:2010 (not modified).
IEC 61158-2:2010	NOTE	Harmonized as EN 61158-2:2010 (not modified).
IEC 61158-3-18	NOTE	Harmonized as EN 61158-3-18.
IEC 61158-5-18:2010	NOTE	Harmonized as EN 61158-5-18:2012 (not modified).
IEC 61158-6-18:2010	NOTE	Harmonized as EN 61158-6-18:2012 (not modified).

- 3 -

Annex ZA

(normative)

Normative references to international publications with their corresponding European publications

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

Publication	Year	Title	<u>EN/HD</u>	<u>Year</u>
ISO/IEC 7498-1	-	Information technology - Open Systems Interconnection - Basic Reference Model: The Basic Model	-	-
ISO/IEC 7498-3	-	Information technology - Open Systems Interconnection - Basic Reference Model: Naming and addressing	-	-
ISO/IEC 13239	2002	Information technology - Telecommunications and information exchange between systems - High-level data link control (HDLC) procedures		-

This page is intentionally left BLANK.

- 2 - 61158-4-18 © IEC:2010(E)

CONTENTS

FO	REWO)RD	5
INT	RODI	JCTION	7
1	Scop	e	8
	1.1	General	8
	1.2	Specifications	8
	1.3	Procedures	
	1.4	Applicability	9
	1.5	Conformance	9
2	Norm	ative references	9
3	Term	s, definitions, symbols, abbreviations and conventions	9
	3.1	Reference model terms and definitions	
	3.2	Type 18: Symbols	
	3.3	Type 18: Additional conventions	
4	DL-p	rotocol overview	
	4.1	Introduction	. 10
	4.2	Polled DLE classes	
	4.3	Packed DLE classes	
5	DLP	DU encoding and transmission	. 11
	5.1	DL – PhL interface	.11
	5.2	DLPDU transmission encoding	
6	DLP	DU – basic structure	
	6.1	Overview	.14
	6.2	Address field	
	6.3	Status field	
	6.4	Data field	
7	DLP	DU – Detailed structure, segmenting and reassembly	. 19
8	Data	transmission methods	.23
	8.1	Overview	
	8.2	Master-polled method	
	8.3	Level A slave-polled method	
	8.4	Level B slave-polled method	
	8.5	Level C slave-polled method	
	8.6	Master-packed method	.26
	8.7	Slave-packed method	.27
9	DL-m	anagement – procedures	.28
	9.1	Overview	.28
	9.2	Establish master-polled DLE procedure	.28
	9.3	Establish slave-polled DLE procedure	.29
	9.4	Establish master-packed DLE procedure	.31
	9.5	Establish slave-packed DLE procedure	.32
	9.6	Release connection procedure	.33
	9.7	Suspend connection procedure	.33
	9.8	Resume connection procedure	.33
	9.9	Activate standby Master procedure	
Bib	liogra	phy	.35

61158-4-18 © IEC:2010(E)	- 3 -
--------------------------	-------

Figure 1 – HDLC flag	. 12
Table 1 – HDLC convention summary	.13
Table 2 – HDLC exception summary	.14
Table 3 – Master-polled DLE address octet 0	.14
Table 4 – Slave-polled DLE address octet 0	. 15
Table 5 – Master-packed DLE address octet 0	. 15
Table 6 – Master-polled DLE status octet 0	. 16
Table 7 – Master-polled DLE status octet 1	.16
Table 8 – Slave-polled DLE status octet 0	. 17
Table 9 – slave-polled DLE status octet 1	. 17
Table 10 – Slave-packed DLE status	.17
Table 11 – DLPDU – Master-polled DLE acyclic data field	. 18
Table 12 – DLPDU – Slave-polled DLE acyclic data field	. 19
Table 13 – Example master-polled DLE RY contiguous data field	.20
Table 14 – Example slave-polled DLE RX contiguous data field	. 20
Table 15 – Example master-polled DLE RWw contiguous data field	. 20
Table 16 – Example slave-polled DLE RWr contiguous data field	.20
Table 17 – Bit-oriented segment header	.21
Table 18 – Polled DLE acyclic segment number field	.22
Table 19 – Slave-polled DLE acyclic data type and sequence field	. 22
Table 20 – DLPDU – Polled class poll with data	.23
Table 21 – Slave-polled DLE response timeout	.23
Table 21 – Slave-polled DLE response timeout Table 22 – DLPDU – Poll	
	.24
Table 22 – DLPDU – Poll	.24 .24
Table 22 – DLPDU – Poll Table 23 – DLPDU – End of cycle	24 24 24
Table 22 – DLPDU – Poll Table 23 – DLPDU – End of cycle Table 24 – slave-polled DLE request timeout	. 24 . 24 . 24 . 25
Table 22 - DLPDU - PollTable 23 - DLPDU - End of cycleTable 24 - slave-polled DLE request timeoutTable 25 - DLPDU - Level A poll response	24 24 24 25 25
Table 22 - DLPDU - PollTable 23 - DLPDU - End of cycleTable 24 - slave-polled DLE request timeoutTable 25 - DLPDU - Level A poll responseTable 26 - DLPDU - Level B poll response	24 24 25 25 26
Table 22 - DLPDU - PollTable 23 - DLPDU - End of cycleTable 24 - slave-polled DLE request timeoutTable 25 - DLPDU - Level A poll responseTable 26 - DLPDU - Level B poll responseTable 27 - DLPDU - Level C poll response	24 24 25 25 26 26
Table 22 - DLPDU - PollTable 23 - DLPDU - End of cycleTable 24 - slave-polled DLE request timeoutTable 25 - DLPDU - Level A poll responseTable 26 - DLPDU - Level B poll responseTable 27 - DLPDU - Level C poll responseTable 28 - DLPDU - Packed class poll with data	. 24 . 24 . 25 . 25 . 25 . 26 . 26 . 26
Table 22 - DLPDU - PollTable 23 - DLPDU - End of cycleTable 24 - slave-polled DLE request timeoutTable 25 - DLPDU - Level A poll responseTable 26 - DLPDU - Level B poll responseTable 27 - DLPDU - Level C poll responseTable 28 - DLPDU - Level C poll responseTable 29 - Slave-packed DLE response timeout	. 24 . 24 . 25 . 25 . 26 . 26 . 26 . 26 . 27
Table 22 - DLPDU - PollTable 23 - DLPDU - End of cycleTable 24 - slave-polled DLE request timeoutTable 25 - DLPDU - Level A poll responseTable 26 - DLPDU - Level B poll responseTable 27 - DLPDU - Level C poll responseTable 28 - DLPDU - Level C poll responseTable 29 - Slave-packed DLE request timeoutTable 30 - Slave-packed DLE request timeout	. 24 . 24 . 25 . 25 . 26 . 26 . 26 . 27 . 27
Table 22 - DLPDU - PollTable 23 - DLPDU - End of cycleTable 24 - slave-polled DLE request timeoutTable 25 - DLPDU - Level A poll responseTable 26 - DLPDU - Level B poll responseTable 27 - DLPDU - Level C poll responseTable 28 - DLPDU - Packed class poll with dataTable 29 - Slave-packed DLE request timeoutTable 30 - Slave-packed DLE request timeoutTable 31 - DLPDU - Packed class poll response	24 24 25 25 26 26 26 27 27 28
Table 22 - DLPDU - PollTable 23 - DLPDU - End of cycleTable 24 - slave-polled DLE request timeoutTable 25 - DLPDU - Level A poll responseTable 26 - DLPDU - Level B poll responseTable 27 - DLPDU - Level C poll responseTable 28 - DLPDU - Packed class poll with dataTable 29 - Slave-packed DLE request timeoutTable 30 - Slave-packed DLE request timeoutTable 31 - DLPDU - Packed class poll responseTable 32 - Slave-packed DLE time constraints	24 24 25 25 26 26 27 27 27 28 28
Table 22 - DLPDU - PollTable 23 - DLPDU - End of cycleTable 24 - slave-polled DLE request timeoutTable 25 - DLPDU - Level A poll responseTable 26 - DLPDU - Level B poll responseTable 27 - DLPDU - Level C poll responseTable 28 - DLPDU - Packed class poll with dataTable 29 - Slave-packed DLE request timeoutTable 30 - Slave-packed DLE request timeoutTable 31 - DLPDU - Packed class poll responseTable 32 - Slave-packed DLE time constraintsTable 33 - DLPDU - Poll with test data	24 24 25 26 26 27 27 28 28 29
Table 22 - DLPDU - PollTable 23 - DLPDU - End of cycleTable 24 - slave-polled DLE request timeoutTable 25 - DLPDU - Level A poll responseTable 26 - DLPDU - Level B poll responseTable 27 - DLPDU - Level C poll responseTable 28 - DLPDU - Packed class poll with dataTable 29 - Slave-packed DLE request timeoutTable 30 - Slave-packed DLE request timeoutTable 31 - DLPDU - Packed class poll responseTable 32 - Slave-packed DLE time constraintsTable 33 - DLPDU - Poll with test dataTable 34 - Slave-polled DLE response timeout	24 24 25 25 26 26 27 27 27 28 28 29 29
Table 22 - DLPDU - PollTable 23 - DLPDU - End of cycleTable 24 - slave-polled DLE request timeoutTable 25 - DLPDU - Level A poll responseTable 26 - DLPDU - Level B poll responseTable 27 - DLPDU - Level C poll responseTable 28 - DLPDU - Packed class poll with dataTable 29 - Slave-packed DLE request timeoutTable 31 - DLPDU - Packed class poll responseTable 32 - Slave-packed DLE time constraintsTable 33 - DLPDU - Poll with test dataTable 34 - Slave-polled DLE response timeout	24 24 25 25 26 26 26 27 27 27 28 29 29 29
Table 22 - DLPDU - PollTable 23 - DLPDU - End of cycleTable 24 - slave-polled DLE request timeoutTable 25 - DLPDU - Level A poll responseTable 26 - DLPDU - Level B poll responseTable 27 - DLPDU - Level C poll responseTable 28 - DLPDU - Packed class poll with dataTable 30 - Slave-packed DLE request timeoutTable 31 - DLPDU - Packed class poll responseTable 32 - Slave-packed DLE time constraintsTable 33 - DLPDU - Poll with test dataTable 34 - Slave-polled DLE response timeoutTable 35 - DLPDU - Poll testTable 36 - Slave-polled DLE request timeout	24 24 25 26 26 26 27 27 28 29 29 29 29 30
Table 22 - DLPDU - PollTable 23 - DLPDU - End of cycleTable 24 - slave-polled DLE request timeoutTable 25 - DLPDU - Level A poll responseTable 26 - DLPDU - Level B poll responseTable 27 - DLPDU - Level C poll responseTable 28 - DLPDU - Packed class poll with dataTable 29 - Slave-packed DLE request timeoutTable 30 - Slave-packed DLE request timeoutTable 31 - DLPDU - Packed class poll responseTable 32 - Slave-packed DLE time constraintsTable 33 - DLPDU - Poll with test dataTable 34 - Slave-polled DLE response timeoutTable 35 - DLPDU - Poll testTable 36 - Slave-polled DLE request timeout	24 24 25 25 26 26 26 27 27 27 28 29 29 29 29 30 30
Table 22 - DLPDU - PollTable 23 - DLPDU - End of cycleTable 24 - slave-polled DLE request timeoutTable 25 - DLPDU - Level A poll responseTable 26 - DLPDU - Level B poll responseTable 27 - DLPDU - Level C poll responseTable 28 - DLPDU - Packed class poll with dataTable 29 - Slave-packed DLE request timeoutTable 30 - Slave-packed DLE request timeoutTable 31 - DLPDU - Packed class poll responseTable 32 - Slave-packed DLE time constraintsTable 33 - DLPDU - Poll with test dataTable 34 - Slave-polled DLE response timeoutTable 35 - DLPDU - Poll testTable 36 - Slave-polled DLE request timeoutTable 37 - DLPDU - Poll test responseTable 37 - DLPDU - Poll test response	24 24 25 26 26 27 27 28 29 29 29 29 30 31

- 4 - 61158-4-18 © IEC:2010(E)

Table 42 – Slave-packed DLE number of occupied DLE station slots	
Table 43 – Slave-packed DLE baud rate synchronization timeout	
Table 44 – Slave-packed DLE Master timeout	
Table 45 – DLPDU – Packed poll test response	

61158-4-18 © IEC:2010(E)

- 5 -

INTERNATIONAL ELECTROTECHNICAL COMMISSION

INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

Part 4-18: Data-link layer protocol specification – Type 18 elements

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committee; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

International Standard IEC 61158-4-18 has been prepared by subcommittee 65C: Industrial networks, of IEC technical committee 65: Industrial-process measurement, control and automation.

This second edition cancels and replaces the first edition published in 2007. This edition constitutes a technical revision.

The main changes with respect to the previous edition are listed below:

- Editorial improvements
- Addition of cyclic data segmenting

- 6 -

61158-4-18 © IEC:2010(E)

The text of this standard is based on the following documents:

FDIS	Report on voting
65C/605/FDIS	65C/619/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with ISO/IEC Directives, Part 2.

A list of all the parts of the IEC 61158 series, published under the general title *Industrial communication networks – Fieldbus specifications*, can be found on the IEC web site.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

NOTE The revision of this standard will be synchronized with the other parts of the IEC 61158 series.

61158-4-18 © IEC:2010(E)

- 7 -

INTRODUCTION

This part of IEC 61158 is one of a series produced to facilitate the interconnection of automation system components. It is related to other standards in the set as defined by the "three-layer" fieldbus reference model described in IEC 61158-1.

The data-link protocol provides the data-link service by making use of the services available from the physical layer. The primary aim of this standard is to provide a set of rules for communication expressed in terms of the procedures to be carried out by peer data-link entities (DLEs) at the time of communication. These rules for communication are intended to provide a sound basis for development in order to serve a variety of purposes:

- a) as a guide for implementors and designers;
- b) for use in the testing and procurement of equipment;
- c) as part of an agreement for the admittance of systems into the open systems environment;
- d) as a refinement to the understanding of time-critical communications within OSI.

This standard is concerned, in particular, with the communication and interworking of sensors, effectors and other automation devices. By using this standard together with other standards positioned within the OSI or fieldbus reference models, otherwise incompatible systems may work together in any combination.

NOTE Use of some of the associated protocol types is restricted by their intellectual-property-right holders. In all cases, the commitment to limited release of intellectual-property-rights made by the holders of those rights permits a particular data-link layer protocol type to be used with physical layer and application layer protocols in Type combinations as specified explicitly in the profile parts. Use of the various protocol types in other combinations may require permission from their respective intellectual-property-right holders.

The International Electrotechnical Commission (IEC) draws attention to the fact that it is claimed that compliance with this document may involve the use of patents concerning Type 18 elements and possibly other types given in 7.1.2 as follows:

3343036/Japan	[MEC]	Network System for a Programmable Controller
5896509/USA	[MEC]	Network System for a Programmable Controller
246906/Korea	[MEC]	Network System for a Programmable Controller
19650753/Germany	[MEC]	Network System for a Programmable Controller

IEC takes no position concerning the evidence, validity and scope of these patent rights.

The holder of thess patent rights has assured the IEC that he/she is willing to negotiate licences either free of charge or under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holder of thess patent rights is registered with IEC. Information may be obtained from:

[MEC]	Mitsubishi Electric Corporation
	Corporate Licensing DeivsionDivision
	7-3, Marunouchi 2-chome, Chiyoda-ku,
	Tokyo 100-8310, Japan

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. IEC shall not be held responsible for identifying any or all such patent rights.

ISO (www.iso.org/patents) and IEC (http://www.iec.ch/tctools/patent_decl.htm) maintain online data bases of patents relevant to their standards. Users are encouraged to consult the data bases for the most up to date information concerning patents.

- 8 -

61158-4-18 © IEC:2010(E)

INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

Part 4-18: Data-link layer protocol specification – Type 18 elements

1 Scope

1.1 General

The data-link layer provides basic time-critical messaging communications between devices in an automation environment.

This protocol provides communication opportunities to all participating data-link entities

- a) in a synchronously-starting cyclic manner, according to a pre-established schedule, and
- b) in a cyclic or acyclic asynchronous manner, as requested each cycle by each of those data-link entities.

Thus this protocol can be characterized as one which provides cyclic and acyclic access asynchronously but with a synchronous restart of each cycle.

1.2 Specifications

This part of IEC 61158 specifies

- a) procedures for the timely transfer of data and control information from one data-link user entity to a peer user entity, and among the data-link entities forming the distributed datalink service provider;
- b) procedures for giving communications opportunities to all participating DL-entities, sequentially and in a cyclic manner for deterministic and synchronized transfer at cyclic intervals up to one millisecond;
- c) procedures for giving communication opportunities available for time-critical data transmission together with non-time-critical data transmission without prejudice to the time-critical data transmission;
- d) procedures for giving cyclic and acyclic communication opportunities for time-critical data transmission with prioritized access;
- e) procedures for giving communication opportunities based on standard ISO/ IEC 8802-3 medium access control, with provisions for nodes to be added or removed during normal operation;
- f) the structure of the fieldbus DLPDUs used for the transfer of data and control information by the protocol of this standard, and their representation as physical interface data units.

1.3 Procedures

The procedures are defined in terms of

- a) the interactions between peer DL-entities (DLEs) through the exchange of fieldbus DLPDUs;
- b) the interactions between a DL-service (DLS) provider and a DLS-user in the same system through the exchange of DLS primitives;
- c) the interactions between a DLS-provider and a Ph-service provider in the same system through the exchange of Ph-service primitives.

-9-

61158-4-18 © IEC:2010(E)

1.4 Applicability

These procedures are applicable to instances of communication between systems which support time-critical communications services within the data-link layer of the OSI or fieldbus reference models, and which require the ability to interconnect in an open systems interconnection environment.

Profiles provide a simple multi-attribute means of summarizing an implementation's capabilities, and thus its applicability to various time-critical communications needs.

1.5 Conformance

This part of IEC 61158 does not specify individual implementations or products, nor do they constrain the implementations of data-link entities within industrial automation systems.

There is no conformance of equipment to this data-link layer service definition standard. Instead, conformance is achieved through implementation of the corresponding data-link protocol that fulfills the Type 18 data-link layer services defined in this standard.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 7498-1, Information technology – Open Systems Interconnection – Basic Reference Model: The Basic Model

ISO/IEC 7498-3, Information technology – Open Systems InterconnectionI – Basic Reference Model: Naming and addressing

ISO/IEC 13239:2002, Information technology – Telecommunications and information exchange between systems – High-level data link control (HDLC) procedures

3 Terms, definitions, symbols, abbreviations and conventions

For the purposes of this document, the following terms, definitions, symbols, abbreviations and conventions apply.

3.1 Reference model terms and definitions

This standard is based in part on the concepts developed in ISO/IEC 7498-1 and ISO/IEC 7498-3, and makes use of the following additional terms:

3.1.1 DLE station identifier

network address assigned to a DLE

3.1.2 DLE station slot

unit (granularity of one) of position dependent mapping (for cyclic data field) of which a DLE may occupy one or more, delineated by the range beginning at the DLE station identifier with a length equal to the configured number of occupied slots

3.1.3 Master DLE

DLE that performs the functions of network master



This is a free preview. Purchase the entire publication at the link below:

Product Page

S Looking for additional Standards? Visit Intertek Inform Infostore

> Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation