



NSAI
Standards

Irish Standard
I.S. EN ISO 717-1:2013

Acoustics - Rating of sound insulation in buildings and of building elements - Part 1: Airborne sound insulation (ISO 717-1:2013)

I.S. EN ISO 717-1:2013

Incorporating amendments/corrigenda/National Annexes issued since publication:

The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:

I.S. xxx: Irish Standard – national specification based on the consensus of an expert panel and subject to public consultation.

S.R. xxx: Standard Recommendation - recommendation based on the consensus of an expert panel and subject to public consultation.

SWIFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.

This document replaces:
EN ISO 717-1:1996

| | |
|--|-------------------------------------|
| <i>This document is based on:</i> EN ISO 717-1:2013 | <i>Published:</i> 15 March, 2013 |
|--|-------------------------------------|

This document was published under the authority of the NSAI and comes into effect on:
15 March, 2013

ICS number:
91.120.20

NSAI
1 Swift Square,
Northwood, Santry
Dublin 9

T +353 1 807 3800
F +353 1 807 3838
E standards@nsai.ie
W NSAI.ie

Sales:
T +353 1 857 6730
F +353 1 857 6729
W standards.ie

Údarás um Chaighdeáin Náisiúnta na hÉireann

English Version

Acoustics - Rating of sound insulation in buildings and of
building elements - Part 1: Airborne sound insulation (ISO 717-
1:2013)

Acoustique - Évaluation de l'isolement acoustique des
immeubles et des éléments de construction - Partie 1:
Isolation aux bruits aériens (ISO 717-1:2013)

Akustik - Bewertung der Schalldämmung in Gebäuden und
von Bauteilen - Teil 1: Luftschalldämmung (ISO 717-
1:2013)

This European Standard was approved by CEN on 5 January 2013.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

Page

Foreword.....3

Foreword

This document (EN ISO 717-1:2013) has been prepared by Technical Committee ISO/TC 43 “Acoustics” in collaboration with Technical Committee CEN/TC 126 “Acoustic properties of building elements and of buildings” the secretariat of which is held by AFNOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by September 2013, and conflicting national standards shall be withdrawn at the latest by September 2013.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 717-1:1996.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Endorsement notice

The text of ISO 717-1:2013 has been approved by CEN as EN ISO 717-1:2013 without any modification.

This page is intentionally left BLANK.

I.S. EN ISO 717-1:2013
INTERNATIONAL
STANDARD

ISO
717-1

Third edition
2013-03-01

**Acoustics — Rating of sound insulation
in buildings and of building elements —**

Part 1:
Airborne sound insulation

*Acoustique — Évaluation de l'isolement acoustique des immeubles et
des éléments de construction —*

Partie 1: Isolement aux bruits aériens



Reference number
ISO 717-1:2013(E)

© ISO 2013



COPYRIGHT PROTECTED DOCUMENT

© ISO 2013

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

| | Page |
|--|-----------|
| Foreword | iv |
| Introduction | v |
| 1 Scope | 1 |
| 2 Normative references | 1 |
| 3 Terms and definitions | 1 |
| 4 Procedure for evaluating single-number quantities | 2 |
| 4.1 General..... | 2 |
| 4.2 Reference values..... | 3 |
| 4.3 Sound spectra..... | 3 |
| 4.4 Method of comparison..... | 3 |
| 4.5 Calculation of spectrum adaptation terms..... | 8 |
| 5 Statement of results | 8 |
| 5.1 General..... | 8 |
| 5.2 Statement of performance of building elements..... | 9 |
| 5.3 Statement of requirements and of performance of buildings..... | 9 |
| Annex A (informative) Use of spectrum adaptation terms | 10 |
| Annex B (informative) Terms and spectra for an enlarged frequency range | 12 |
| Annex C (informative) Examples of the calculation of single-number quantities and spectrum adaptation terms | 15 |
| Bibliography | 18 |

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 717-1 was prepared by Technical Committee ISO/TC 43, *Acoustics*, Subcommittee SC 2, *Building acoustics*.

This third edition cancels and replaces the second edition (ISO 717-1:1996), which has been technically revised. It also incorporates the Amendment ISO 717-1:1996/Amd. 1:2006.

The purpose of this revised version is to:

- allow weighting steps of 0,1 dB to be used for expression of uncertainty;
- update references.

ISO 717 consists of the following parts, under the general title *Acoustics — Rating of sound insulation in buildings and of building elements*:

- *Part 1: Airborne sound insulation*
- *Part 2: Impact sound insulation*

Introduction

Methods of measurement of airborne sound insulation of building elements and in buildings have been standardized e.g. in ISO 10140-2, ISO 140-4, and ISO 140-5. The purpose of this part of ISO 717 is to standardize a method whereby the frequency-dependent values of airborne sound insulation can be converted into a single number characterizing the acoustical performance.

References to standards which provide data for single-number evaluation are meant to be examples and therefore are not complete.

Acoustics — Rating of sound insulation in buildings and of building elements —

Part 1: Airborne sound insulation

1 Scope

This part of ISO 717:

- a) defines single-number quantities for airborne sound insulation in buildings and of building elements such as walls, floors, doors, and windows;
- b) takes into consideration the different sound level spectra of various noise sources such as noise sources inside a building and traffic outside a building;
- c) gives rules for determining these quantities from the results of measurements carried out in one-third-octave or octave bands in accordance with ISO 10140-2, ISO 140-4, and ISO 140-5.

The single-number quantities in accordance with this part of ISO 717 are intended for rating airborne sound insulation and for simplifying the formulation of acoustical requirements in building codes. An additional single-number evaluation in steps of 0,1 dB is indicated for the expression of uncertainty (except for spectrum adaptation terms). The required numerical values of the single-number quantities are specified according to varying needs. The single-number quantities are based on results of measurements in one-third-octave bands or octave bands.

For laboratory measurements made in accordance with ISO 10140, single-number quantities should be calculated using one-third-octave bands only.

The rating of results of measurements carried out over an enlarged frequency range is dealt with in [Annex B](#).

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 140-4:1998, *Acoustics — Measurement of sound insulation in buildings and of building elements — Part 4: Field measurements of airborne sound insulation between rooms*

ISO 140-5:1998, *Acoustics — Measurement of sound insulation in buildings and of building elements — Part 5: Field measurements of airborne sound insulation of façade elements and façades*

ISO 10140-2:2010, *Acoustics — Laboratory measurement of sound insulation of building elements — Part 2: Measurement of airborne sound insulation*

ISO 10848-2:2006, *Acoustics — Laboratory measurement of the flanking transmission of airborne and impact sound between adjoining rooms — Part 2: Application to light elements when the junction has a small influence*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO 717-1:2013(E)

3.1 single-number quantity for airborne sound insulation rating
value, in decibels, of the reference curve at 500 Hz after shifting it in accordance with the method specified in this part of ISO 717

Note 1 to entry: Terms and symbols for the single-number quantity used depend on the type of measurement. Examples are listed in [Table 1](#) for airborne sound insulation properties of building elements and in [Table 2](#) for airborne sound insulation in buildings. In general, new single-number quantities are derived in a similar way.

3.2 spectrum adaptation term
value, in decibels, to be added to the single-number rating (e.g. R_w) to take account of the characteristics of particular sound spectra

Note 1 to entry: Two sound spectra are defined (in one-third-octave bands and in octave bands) in this part of ISO 717.

Note 2 to entry: [Annex A](#) gives information on the purpose of introducing these two spectrum adaptation terms.

Table 1 — Single-number quantities of airborne sound insulation properties of building elements

| Derived from one-third-octave band values | | Defined in | |
|--|---|------------------|-------------|
| Single-number quantity | Term and symbol | | |
| Weighted sound reduction index, R_w | Sound reduction index, R | ISO 10140-2:2010 | Formula (2) |
| Weighted normalized flanking level difference, $D_{n,f,w}$ | Normalized flanking level difference, $D_{n,f}$ | ISO 10848-2:2006 | Formula (1) |
| Weighted element-normalized level difference, $D_{n,e,w}$ | Element-normalized level difference, $D_{n,e}$ | ISO 10140-2:2010 | Formula (5) |

Table 2 — Single-number quantities of airborne sound insulation in buildings

| Derived from one-third-octave or octave band values | | Defined in | |
|--|---|----------------|-------------|
| Single-number quantity | Term and symbol | | |
| Weighted apparent sound reduction index, R'_w | Apparent sound reduction index, R' | ISO 140-4:1998 | Formula (5) |
| Weighted apparent sound reduction index, $R'_{45^\circ,w}$ | Apparent sound reduction index, R'_{45° | ISO 140-5:1998 | Formula (3) |
| Weighted apparent sound reduction index, $R'_{tr,s,w}$ | Apparent sound reduction index, $R'_{tr,s}$ | ISO 140-5:1998 | Formula (4) |
| Weighted normalized level difference, $D_{n,w}$ | Normalized level difference, D_n | ISO 140-4:1998 | Formula (3) |
| Weighted standardized level difference, $D_{nT,w}$ | Standardized level difference, D_{nT} | ISO 140-4:1998 | Formula (4) |
| Weighted standardized level difference, $D_{ls,2m,nT,w}$ or $D_{tr,2m,nT,w}$ | Standardized level difference, $D_{ls,2m,nT}$ or $D_{tr,2m,nT}$ | ISO 140-5:1998 | Formula (7) |

4 Procedure for evaluating single-number quantities

4.1 General

The values obtained in accordance with ISO 10140-2, ISO 140-4, and ISO 140-5 are compared with reference values (see [4.2](#)) at the frequencies of measurement within the range 100 Hz to 3 150 Hz for one-third-octave bands and 125 Hz to 2 000 Hz for octave bands.

The comparison shall be carried out as specified in [4.4](#).

Furthermore, two spectrum adaptation terms shall be calculated (see [4.5](#)) based on two typical spectra within the frequency range as quoted above. These two terms may optionally be supplemented by additional spectrum adaptation terms covering (if need be and if measured data are available) a wider frequency range between 50 Hz and 5 000 Hz.

4.2 Reference values

The set of reference values used for comparison with measurement results shall be as given in [Table 3](#). The reference curves are shown in [Figure 1](#) and [Figure 2](#).

Table 3 — Reference values for airborne sound

| Frequency Hz | Reference values dB | |
|-----------------|---------------------------|--------------|
| | One-third-octave bands | Octave bands |
| 100 | 33 | 36 |
| 125 | 36 | |
| 160 | 39 | |
| 200 | 42 | 45 |
| 250 | 45 | |
| 315 | 48 | |
| 400 | 51 | 52 |
| 500 | 52 | |
| 630 | 53 | |
| 800 | 54 | 55 |
| 1 000 | 55 | |
| 1 250 | 56 | |
| 1 600 | 56 | 56 |
| 2 000 | 56 | |
| 2 500 | 56 | |
| 3 150 | 56 | |

4.3 Sound spectra

The set of sound spectra in one-third-octave bands and octave bands to calculate the spectrum adaptation terms shall be as given in [Table 4](#) and shown in [Figure 3](#) and [Figure 4](#). The spectra are A-weighted and the overall spectrum level is normalized to 0 dB.

4.4 Method of comparison

To evaluate the results of a measurement made in accordance with ISO 10140-2, ISO 140-4, and ISO 140-5 in one-third-octave bands (or octave bands), the measurement data shall be given to one decimal place.¹⁾ Shift the relevant reference curve in increments of 1 dB (0,1 dB for the expression of uncertainty) towards the measured curve until the sum of unfavourable deviations is as large as possible, but not more than 32,0 dB (measurement in 16 one-third-octave bands) or 10,0 dB (measurement in 5 octave bands).

1) The different parts of ISO 140 state that the results shall be reported “to one decimal place”. However, if the octave or one-third-octave values have been reported with more than one decimal digit, the values shall be reduced to one decimal place before use in the calculation of the single number rating. This is done by taking the value in tenths of a decibel closest to the reported values: XX,XYZ ZZ ... is rounded to XX,X if Y is less than 5 and to XX,X + 0,1 if Y is equal to or greater than 5. Software developers should ensure that this reduction applies to the true input values and not only to the displayed precision (as shown on the screen or printed on paper). Generally this can be implemented by the following sequence of instructions: multiply the (positive) number XX,XYZ ZZ ... by 10 and add 0,5, take the integer part and then divide the result by 10. For further details see ISO 80000-1.[1]

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

-
- [Looking for additional Standards? Visit Intertek Inform Infostore](#)
 - [Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation](#)
-