



NSAI
Standards

Irish Standard
I.S. EN 50464-1:2007

Three-phase oil-immersed distribution transformers 50 Hz, from 50 kVA to 2 500 kVA with highest voltage for equipment not exceeding 36 kV -- Part 1: General requirements

I.S. EN 50464-1:2007

Incorporating amendments/corrigenda issued since publication:

EN 50464-1:2007/A1:2012

The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:

I.S. xxx: Irish Standard – national specification based on the consensus of an expert panel and subject to public consultation.

S.R. xxx: Standard Recommendation - recommendation based on the consensus of an expert panel and subject to public consultation.

SWiFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.

<i>This document replaces:</i> HD 428.1 S1:1992 + A1:1995 HD 428.3 S1:1994	<i>This document is based on:</i> EN 50464-1:2007 HD 428.3 S1:1994	<i>Published:</i> 20 April, 2007 3 March, 1994
This document was published under the authority of the NSAI and comes into effect on: 9 May, 2007		ICS number: 29.180
NSAI 1 Swift Square, Northwood, Santry Dublin 9	T +353 1 807 3800 F +353 1 807 3838 E standards@nsai.ie W NSAI.ie	Sales: T +353 1 857 6730 F +353 1 857 6729 W standards.ie
Údarás um Chaighdeáin Náisiúnta na hÉireann		

**Three-phase oil-immersed distribution transformers 50 Hz, from 50 kVA to 2 500 kVA with highest voltage for equipment not exceeding 36 kV -
Part 1: General requirements**

Transformateurs triphasés de distribution immergés dans l'huile, 50 Hz, de 50 kVA à 2 500 kVA, de tension la plus élevée pour le matériel ne dépassant pas 36 kV -
Partie 1: Prescriptions générales

Ölgefüllte Drehstrom-Verteilungstransformatoren 50 Hz, 50 kVA bis 2 500 kVA, mit einer höchsten Spannung für Betriebsmittel bis 36 kV -
Teil 1: Allgemeine Anforderungen

This amendment A1 modifies the European Standard EN 50464-1:2007; it was approved by CENELEC on 2011-10-31. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this amendment the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This amendment exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Management Centre: Avenue Marnix 17, B - 1000 Brussels

Foreword

This document (EN 50464-1:2007/A1:2012) has been prepared by CLC/TC 14, "Power transformers".

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2012-10-31
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2014-10-31

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

EUROPEAN STANDARD

EN 50464-1

NORME EUROPÉENNE

EUROPÄISCHE NORM

April 2007

ICS 29.180

Supersedes HD 428.1 S1:1992 + A1:1995 and HD 428.3 S1:1994

English version

**Three-phase oil-immersed distribution transformers 50 Hz,
from 50 kVA to 2 500 kVA with highest voltage
for equipment not exceeding 36 kV -
Part 1: General requirements**

Transformateurs triphasés de distribution
immergés dans l'huile,
50 Hz, de 50 kVA à 2 500 kVA,
de tension la plus élevée
pour le matériel ne dépassant pas 36 kV -
Partie 1: Prescriptions générales

Ölgefüllte
Drehstrom-Verteilungstransformatoren
50 Hz, 50 kVA bis 2 500 kVA,
mit einer höchsten Spannung
für Betriebsmittel bis 36 kV -
Teil 1: Allgemeine Anforderungen

This European Standard was approved by CENELEC on 2006-12-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: rue de Stassart 35, B - 1050 Brussels

Foreword

This European Standard, prepared by the Technical Committee CENELEC TC 14, Power transformers was submitted to the formal vote and was approved by CENELEC as EN 50464-1 on 2006-12-01.

This European Standard supersedes HD 428.1 S1:1992 + A1:1995 and HD 428.3 S1:1994.

The following dates were fixed:

- latest date by which the EN has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2007-12-01
- latest date by which the national standards conflicting with the EN have to be withdrawn (dow) 2011-12-01

The EN 50464 series consists of the following parts, under the general title “Three-phase oil-immersed distribution transformers 50 Hz, from 50 kVA to 2 500 kVA with highest voltage for equipment not exceeding 36 kV”:

- Part 1 General requirements
 - Part 2-1 Distribution transformers with cable boxes on the high-voltage and/or low-voltage side – General requirements
 - Part 2-2 Distribution transformers with cable boxes on the high-voltage and/or low-voltage side – Cable boxes type 1 for use on distribution transformers meeting the requirements of EN 50464-2-1
 - Part 2-3 Distribution transformers with cable boxes on the high-voltage and/or low-voltage side – Cable boxes type 2 for use on distribution transformers meeting the requirements of EN 50464-2-1
 - Part 3 Determination of the power rating of a transformer loaded with non-sinusoidal currents
 - Part 4 Requirements and tests concerning pressurised corrugated tanks
-

Contents

1	Scope.....	4
2	Normative references	4
3	Electrical characteristics	4
3.1	Rated power.....	4
3.2	Highest voltages for equipment for windings	5
3.3	Rated voltages of windings	5
3.4	Tapping	5
3.5	Connections	5
3.6	Dimensioning of neutral connection of the low-voltage winding	6
3.7	Short-circuit impedance	6
3.8	Losses and sound power level.....	6
3.9	Tolerances and penalties	10
3.10	Tests	10
3.11	Insulation levels and dielectric tests	10
4	Design requirements	10
4.1	Type of oil preservation system and degree of sealing.....	10
4.2	Terminal markings	10
4.3	Terminations	10
4.4	Distance between bushings.....	11
4.5	Rollers	11
5	Accessories	11
6	Efficiency and voltage drop (at reference temperature).....	12
6.1	Efficiency	12
6.2	Voltage drop ($u\%$)	13
	Annex A (informative) Capitalisation evaluation.....	14
	Bibliography.....	15

Tables

Table 1	– Connections for distribution transformers.....	5
Table 2	– Load losses P_k (W) at 75 °C for $U_m = 24$ kV.....	7
Table 3	– No load losses P_0 (W) and sound power level ($L_{W(A)}$) for $U_m = 24$ kV.....	8
Table 4	– Load losses P_{k36} (W) at 75 °C for $U_m = 36$ kV.....	9
Table 5	– No load losses P_{036} (W) and sound power level ($L_{W(A)}$) for $U_m = 36$ kV.....	9
Table 6	– Accessories	12

1 Scope

This document covers transformers from 50 kVA to 2 500 kVA intended for operation in three-phase distribution networks, for indoor or outdoor continuous service, 50 Hz, immersed in mineral oil, natural cooling, with two windings:

- a primary (high-voltage) winding with a highest voltage for equipment from 3,6 kV to 36 kV;
- a secondary (low-voltage) winding with a highest voltage for equipment not exceeding 1,1 kV.

NOTE 1 This document may be applied, either as a whole or in part, to transformers immersed in a synthetic insulating liquid.

NOTE 2 This document may be applied, either as whole or in part, to transformers having windings with more than one rated voltage. In this case the rated power for each rated voltage shall be specified by the purchaser.

The object of this document is to lay down requirements related to electrical characteristics and design of three phases distribution transformers immersed in mineral oil.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 50216	series	Power transformer and reactor fittings
EN 50464-2	series	Three-phase oil-immersed distribution transformers 50 Hz, from 50 kVA to 2500 kVA with highest voltage for equipment not exceeding 36 kV
EN 60076	series	Power transformers (IEC 60076 series)
IEC/TR 60616		Terminal and tapping markings for power transformers

3 Electrical characteristics

3.1 Rated power

The values of the rated power are

50 kVA – 100 kVA – 160 kVA – 250 kVA – 315 kVA – 400 kVA – 500 kVA – 630 kVA –
800 kVA – 1 000 kVA – 1 250 kVA – 1 600 kVA – 2 000 kVA – 2 500 kVA.

The underlined values are preferred.

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

-
- [Looking for additional Standards? Visit Intertek Inform Infostore](#)
 - [Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation](#)
-