



NSAI
Standards

Irish Standard
I.S. EN 12881-1:2014

Conveyor belts - Fire simulation flammability testing - Part 1: Propane burner tests

I.S. EN 12881-1:2014

Incorporating amendments/corrigenda/National Annexes issued since publication:

The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:

I.S. xxx: Irish Standard — national specification based on the consensus of an expert panel and subject to public consultation.

S.R. xxx: Standard Recommendation — recommendation based on the consensus of an expert panel and subject to public consultation.

SWiFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.

This document replaces/revises/consolidates the NSAI adoption of the document(s) indicated on the CEN/CENELEC cover/Foreword and the following National document(s):

NOTE: The date of any NSAI previous adoption may not match the date of its original CEN/CENELEC document.

This document is based on:

EN 12881-1:2014

Published:

2014-05-14

*This document was published
under the authority of the NSAI
and comes into effect on:*

2014-05-31

ICS number:

13.220.40

53.040.20

NOTE: If blank see CEN/CENELEC cover page

NSAI
1 Swift Square,
Northwood, Santry
Dublin 9

T +353 1 807 3800
F +353 1 807 3838
E standards@nsai.ie
W NSAI.ie

Sales:
T +353 1 857 6730
F +353 1 857 6729
W standards.ie

Údarás um Chaighdeáin Náisiúnta na hÉireann

EUROPEAN STANDARD

EN 12881-1

NORME EUROPÉENNE

EUROPÄISCHE NORM

May 2014

ICS 13.220.40; 53.040.20

Supersedes EN 12881-1:2005+A1:2008

English Version

Conveyor belts - Fire simulation flammability testing - Part 1: Propane burner tests

Courroies transporteuses - Essais de simulation
d'inflammation - Partie 1: Essais avec brûleur propane

Fördergurte - Brandtechnische Prüfungen - Teil 1:
Prüfungen mit dem Propanbrenner

This European Standard was approved by CEN on 15 February 2014.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

Page

Foreword.....	3
Introduction	4
1 Scope	5
2 Normative references	5
3 Propane gas supply.....	5
4 Method A – Two metre single burner test	6
4.1 Apparatus	6
4.2 Preparation of test pieces	9
4.3 Temperature at commencement of test	9
4.4 Number of tests.....	9
4.5 Procedure	9
4.6 Termination of tests.....	10
4.7 Measurement of damage to test pieces	10
4.8 Test report	11
5 Method B – Double burner test	12
5.1 Apparatus	12
5.2 Preparation of test pieces	13
5.3 Temperature at commencement of test	13
5.4 Number of tests.....	13
5.5 Procedure	14
5.6 Termination of tests.....	14
5.7 Measurement of damage to test pieces	14
5.8 Test report	15
6 Method C – Mid-scale fire propagation test	15
6.1 Apparatus	15
6.2 Preparation of test pieces	23
6.3 Installation of the test pieces and burner	23
6.4 Temperature at commencement of test	23
6.5 Number of tests.....	23
6.6 Procedure	23
6.7 Termination of tests.....	24
6.8 Measurement of damage to test pieces	24
6.9 Exhaust temperature calibration	25
6.10 Test report	25
7 Method D Laboratory scale Fire Propagation Test	26
7.1 Apparatus	26
7.2 Preparation of test pieces	27
7.3 Installation of the test piece and burner	27
7.4 Test Conditions.....	27
7.5 Procedure	27
7.6 Termination of tests.....	28
7.7 Measurement of damage to test pieces	28
7.8 Test report	28
Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2006/42/EC	33
Bibliography.....	34

Foreword

This document (EN 12881-1:2014) has been prepared by Technical Committee CEN/TC 188 “Conveyor belts”, the secretariat of which is held by SNV.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by November 2014 and conflicting national standards shall be withdrawn at the latest by November 2014.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 12881-1:2005+A1:2008.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

For relationship with EU Directive(s), see informative Annex ZA, which is an integral part of this document.

The main changes with respect to the previous edition are listed below:

- ‘Laboratory scale fire propagation test’ was added (Method D);
- ‘Mid-scale fire propagation test’ (Method C, 6.1.1 Test gallery) thermal conductivity of the refractory material was included;
- ‘Mid-scale fire propagation test’ (Method C, 6.1.4 Gas burner) the diameter of the bore jets used was added.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

EN 12881-1:2014 (E)

Introduction

This European Standard is a type B1 standard as stated in EN ISO 12100.

The provisions of this European Standard may be supplemented or modified by a type C standard.

The machinery concerned and the extent to which hazards, hazardous situations and events are covered are indicated in the scope of this European Standard.

NOTE For machines which are covered by the scope of a type C standard and which have been designed and built according to the provisions of that standard, the provisions of that type C standard take precedence over the provisions of this type B1 standard.

The methods of test described in EN 12881-1 are intended to provide an indication of the reaction of a conveyor belt to a fire situation. However, in doing so attention is drawn to the fact that in assessing the overall flammability characteristics of conveyor belting for specific installations, it is not sufficient to rely solely on any single method of test but consideration has also to be given to the individual site location.

WARNING — The tests described in EN 12881-1 can generate large amounts of smoke and heat. It is therefore essential to conduct the tests with caution, having due regard to health and safety considerations and to terminate any test immediately if at any time it is considered advisable to do so. In this regard it is recommended that no test should be supervised by only one person.

1 Scope

EN 12881-1 describes four methods for measuring the propagation of a flame along a conveyor belt which has been exposed to a relatively high localized heat source such as a fire. The damage suffered by the conveyor belt, as well as its tendency to support combustion, is measured by observing the extent to which the fire spreads along the test piece.

Method A uses a test piece 2 m in length and consumes propane gas through the burner at the rate of $(1,30 \pm 0,05)$ kg per 10 min.

Method B uses a test piece 2,5 m in length and consumes propane gas through two burners mounted above and below the test piece trestle at the rate of $(1,30 \pm 0,05)$ kg per 10 min for each burner.

Method C uses a test piece 1,5 m in length and consumes propane gas through the burner at the rate of (565 ± 10) g per 50 min.

Method D uses a test piece 1,2 m in length and consumes propane gas through the burner at the rate of 150 l/hr (D1) or 190 l/hr (D2).

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 10088-3, *Stainless steels — Part 3: Technical delivery conditions for semi-finished products, bars, rods, wire, sections and bright products of corrosion resisting steels for general purposes*

EN 22768-1, *General tolerances — Part 1: Tolerances for linear and angular dimensions without individual tolerance indications (ISO 2768-1)*

ISO 65, *Carbon steel tubes suitable for screwing in accordance with ISO 7-1*

ISO 9162, *Petroleum products — Fuels (class F) — Liquefied petroleum gases — Specifications*

3 Propane gas supply

The burners used in each method shall be supplied from bottled propane gas complying with ISO 9162 which shall be fed to each burner, using high pressure propane hose having a minimum internal diameter of 6,3 mm, either:

- a) through a pressure reducing valve, a non-return valve and an orifice plate 1,7 mm thick with a 2,5 mm diameter hole; or
- b) through a pressure reducing valve and a non-return valve followed by a flow meter calibrated to ensure that the correct mass of gas is consumed.

Before and during the test, immerse each gas cylinder to approximately two-thirds of its height in a bath of water at a temperature of (25 ± 3) °C. Ensure that each gas cylinder is not emptied at the end of a test by more than 90 % of its gas mass capacity.

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

-
- Looking for additional Standards? Visit Intertek Inform Infostore
 - Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation
-