



NSAI
Standards

Irish Standard
I.S. EN 60728-3:2011

Cable networks for television signals,
sound signals and interactive services
-- Part 3: Active wideband equipment
for cable networks (IEC 60728-3:2010
(EQV))

I.S. EN 60728-3:2011

Incorporating amendments/corrigenda issued since publication:

The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:

I.S. xxx: Irish Standard – national specification based on the consensus of an expert panel and subject to public consultation.

S.R. xxx: Standard Recommendation - recommendation based on the consensus of an expert panel and subject to public consultation.

SWiFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.

| | | |
|--|---|---|
| <i>This document replaces:</i> EN 60728-3:2006 | <i>This document is based on:</i> EN 60728-3:2011 EN 60728-3:2006 | <i>Published:</i> 25 February, 2011 25 April, 2006 |
| This document was published under the authority of the NSAI and comes into effect on: 2 March, 2011 | | ICS number: 33.060.40 33.170 |
| NSAI 1 Swift Square, Northwood, Santry Dublin 9 | T +353 1 807 3800 F +353 1 807 3838 E standards@nsai.ie W NSAI.ie | Sales: T +353 1 857 6730 F +353 1 857 6729 W standards.ie |
| Údarás um Chaighdeáin Náisiúnta na hÉireann | | |

English version

Cable networks for television signals, sound signals and interactive services -

**Part 3: Active wideband equipment for cable networks
(IEC 60728-3:2010)**

Réseaux de distribution par câbles pour signaux de télévision, signaux de radiodiffusion sonore et services interactifs -
Partie 3: Matériel actif à large bande pour réseaux de distribution par câbles
(CEI 60728-3:2010)

Kabelnetze für Fernsehsignale, Tonsignale und interaktive Dienste -
Teil 3: Aktive Breitbandgeräte für koaxiale Kabelnetze
(IEC 60728-3:2010)

This European Standard was approved by CENELEC on 2011-01-13. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Management Centre: Avenue Marnix 17, B - 1000 Brussels

Foreword

The text of document 100/1746/FDIS, future edition 4 of IEC 60728-3, prepared by Technical Area 5, Cable networks for television signals, sound signals and interactive services, of IEC TC 100, Audio, video and multimedia systems and equipment, was submitted to the IEC-CENELEC parallel vote and was approved by CENELEC as EN 60728-3 on 2011-01-13.

This European Standard supersedes EN 60728-3:2006.

EN 60728-3:2011 includes the following significant technical changes with respect to EN 60728-3:2006:

- extension of upper frequency range limit for cable network equipment from 862 MHz to 1 000 MHz;
- method of measurement and requirements for immunity to surge voltages;
- extension of scope to equipment using symmetrical ports;
- additional normative references;
- additional terms and definitions and abbreviations.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN and CENELEC shall not be held responsible for identifying any or all such patent rights.

The following dates were fixed:

- latest date by which the EN has to be implemented
at national level by publication of an identical
national standard or by endorsement (dop) 2011-10-13
- latest date by which the national standards conflicting
with the EN have to be withdrawn (dow) 2014-01-13

Annex ZA has been added by CENELEC.

Endorsement notice

The text of the International Standard IEC 60728-3:2010 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

| | | |
|------------------|------|---|
| IEC 60728-6:2003 | NOTE | Harmonized as EN 60728-6:2003 (not modified). |
| IEC 60728-10 | NOTE | Harmonized as EN 60728-10. |
| IEC 61169-2 | NOTE | Harmonized as EN 61169-2. |
| IEC 61169-24 | NOTE | Harmonized as EN 61169-24. |

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

| <u>Publication</u> | <u>Year</u> | <u>Title</u> | <u>EN/HD</u> | <u>Year</u> |
|--------------------|-------------|---|---------------|-------------|
| IEC 60065 | - | Audio, video and similar electronic apparatus - Safety requirements | EN 60065 | - |
| IEC 60068-1 | 1988 | Environmental testing - Part 1: General and guidance | EN 60068-1 | 1994 |
| IEC 60068-2-1 | - | Environmental testing - Part 2-1: Tests - Test A: Cold | EN 60068-2-1 | - |
| IEC 60068-2-2 | - | Environmental testing - Part 2-2: Tests - Test B: Dry heat | EN 60068-2-2 | - |
| IEC 60068-2-6 | - | Environmental testing - Part 2-6: Tests - Test Fc: Vibration (sinusoidal) | EN 60068-2-6 | - |
| IEC 60068-2-14 | - | Environmental testing - Part 2-14: Tests - Test N: Change of temperature | EN 60068-2-14 | - |
| IEC 60068-2-27 | - | Environmental testing - Part 2-27: Tests - Test Ea and guidance: Shock | EN 60068-2-27 | - |
| IEC 60068-2-29 | - | Environmental testing - Part 2: Tests - Test Eb and guidance: Bump | EN 60068-2-29 | - |
| IEC 60068-2-30 | - | Environmental testing - Part 2-30: Tests - Test Db: Damp heat, cyclic (12 h + 12 h cycle) | EN 60068-2-30 | - |
| IEC 60068-2-31 | - | Environmental testing - Part 2-31: Tests - Test Ec: Rough handling shocks, primarily for equipment-type specimens | EN 60068-2-31 | - |
| IEC 60068-2-32 | - | Environmental testing. Part 2-32: Tests. Test Ed: Free fall | EN 60068-2-32 | - |
| IEC 60068-2-40 | - | Basic environmental testing procedures - Part 2-40: Tests - Test Z/AM: Combined cold/low air pressure tests | EN 60068-2-40 | - |
| IEC 60068-2-48 | - | Environmental testing - Part 2-48: Tests - Guidance on the application of the tests of IEC 60068 to simulate the effects of storage | EN 60068-2-48 | - |
| IEC 60529 | - | Degrees of protection provided by enclosures - (IP Code) | - | - |

I.S. EN 60728-3:2011

EN 60728-3:2011

- 4 -

| <u>Publication</u> | <u>Year</u> | <u>Title</u> | <u>EN/HD</u> | <u>Year</u> |
|----------------------------|-------------|---|--------------|-------------|
| IEC 60728-1 | - | Cable networks for television signals, sound signals and interactive services - Part 1: System performance of forward paths | EN 60728-1 | - |
| IEC 60728-2 | - | Cabled distribution systems for television and sound signals - Part 2: Electromagnetic compatibility for equipment | EN 50083-2 | - |
| IEC 60728-4 | - | Cable networks for television signals, sound signals and interactive services - Part 4: Passive wideband equipment for coaxial cable networks | EN 60728-4 | - |
| IEC 60728-5 | - | Cable networks for television signals, sound signals and interactive services - Part 5: Headend equipment | EN 60728-5 | - |
| IEC 60728-11 | - | Cable networks for television signals, sound signals and interactive services - Part 11: Safety | EN 60728-11 | - |
| IEC 60950-1 | - | Information technology equipment - Safety - Part 1: General requirements | EN 60950-1 | - |
| IEC 61000-4-5 | - | Electromagnetic compatibility (EMC) - Part 4-5: Testing and measurement techniques - Surge immunity test | EN 61000-4-5 | - |
| IEC 61319-1 | - | Interconnections of satellite receiving equipment - Part 1: Europe | EN 61319-1 | - |
| IEC 61319-2 | - | Interconnections of satellite receiving equipment - Part 2: Japan | - | - |
| ITU-T Recommendation G.117 | - | Transmission aspects of unbalance about earth | - | - |
| ITU-T Recommendation O.9 | - | Measuring arrangements to assess the degree of unbalance about earth | - | - |

CONTENTS

| | |
|---|----|
| FOREWORD..... | 6 |
| INTRODUCTION..... | 8 |
| 1 Scope..... | 9 |
| 2 Normative references..... | 9 |
| 3 Terms, definitions, symbols and abbreviations..... | 11 |
| 3.1 Terms and definitions..... | 11 |
| 3.2 Symbols..... | 15 |
| 3.3 Abbreviations..... | 16 |
| 4 Methods of measurement..... | 17 |
| 4.1 General..... | 17 |
| 4.2 Linear distortion..... | 18 |
| 4.2.1 Return loss..... | 18 |
| 4.2.2 Flatness..... | 19 |
| 4.2.3 Chrominance/luminance delay inequality for PAL/SECAM only..... | 19 |
| 4.3 Non-linear distortion..... | 20 |
| 4.3.1 General..... | 20 |
| 4.3.2 Types of measurements..... | 20 |
| 4.3.3 Intermodulation..... | 20 |
| 4.3.4 Composite triple beat..... | 22 |
| 4.3.5 Composite second order beat..... | 25 |
| 4.3.6 Composite crossmodulation..... | 26 |
| 4.3.7 Method of measurement of non-linearity for pure digital channel load..... | 29 |
| 4.3.8 Hum modulation of carrier..... | 29 |
| 4.4 Automatic gain and slope control step response..... | 33 |
| 4.4.1 Definitions..... | 33 |
| 4.4.2 Equipment required..... | 33 |
| 4.4.3 Connection of equipment..... | 34 |
| 4.4.4 Measurement procedure..... | 34 |
| 4.5 Noise figure..... | 35 |
| 4.5.1 General..... | 35 |
| 4.5.2 Equipment required..... | 35 |
| 4.5.3 Connection of equipment..... | 35 |
| 4.5.4 Measurement procedure..... | 35 |
| 4.6 Crosstalk attenuation..... | 36 |
| 4.6.1 Crosstalk attenuation for loop through ports..... | 36 |
| 4.6.2 Crosstalk attenuation for output ports..... | 36 |
| 4.7 Signal level for digitally modulated signals..... | 38 |
| 4.8 Measurement of composite intermodulation noise ratio (<i>CINR</i>)..... | 38 |
| 4.8.1 General..... | 38 |
| 4.8.2 Equipment required..... | 38 |
| 4.8.3 Connection of equipment..... | 39 |
| 4.8.4 Measurement procedure..... | 40 |
| 4.8.5 Presentation of the results..... | 40 |
| 4.9 Immunity to surge voltages..... | 41 |
| 4.9.1 General..... | 41 |
| 4.9.2 Equipment required..... | 42 |

| | | |
|--------|---|----|
| 4.9.3 | Connection of equipment..... | 42 |
| 4.9.4 | Measurement procedure..... | 42 |
| 5 | Equipment requirements..... | 42 |
| 5.1 | General requirements..... | 42 |
| 5.2 | Safety..... | 43 |
| 5.3 | Electromagnetic compatibility (EMC) | 43 |
| 5.4 | Frequency range | 43 |
| 5.5 | Impedance and return loss | 43 |
| 5.6 | Gain | 44 |
| 5.6.1 | Minimum and maximum gain..... | 44 |
| 5.6.2 | Gain control..... | 44 |
| 5.6.3 | Slope and slope control | 44 |
| 5.7 | Flatness | 44 |
| 5.8 | Test points | 45 |
| 5.9 | Group delay..... | 45 |
| 5.9.1 | Chrominance/luminance delay inequality | 45 |
| 5.9.2 | Chrominance/luminance delay inequality for other television standards and modulation systems | 45 |
| 5.10 | Noise figure..... | 45 |
| 5.11 | Non-linear distortion | 45 |
| 5.11.1 | General | 45 |
| 5.11.2 | Second order distortion..... | 45 |
| 5.11.3 | Third order distortion | 45 |
| 5.11.4 | Composite triple beat..... | 46 |
| 5.11.5 | Composite second order..... | 46 |
| 5.11.6 | Composite crossmodulation | 46 |
| 5.11.7 | Maximum operating level for pure digital channel load | 46 |
| 5.12 | Automatic gain and slope control..... | 46 |
| 5.13 | Hum modulation | 46 |
| 5.14 | Power supply..... | 46 |
| 5.15 | Environmental | 47 |
| 5.15.1 | General | 47 |
| 5.15.2 | Storage (simulated effects of)..... | 47 |
| 5.15.3 | Transportation | 47 |
| 5.15.4 | Installation or maintenance..... | 47 |
| 5.15.5 | Operation | 47 |
| 5.15.6 | Energy efficiency of equipment..... | 47 |
| 5.16 | Marking | 47 |
| 5.16.1 | Marking of equipment | 47 |
| 5.16.2 | Marking of ports..... | 47 |
| 5.17 | Mean operating time between failure (MTBF) | 48 |
| 5.18 | Requirements for multi-switches..... | 48 |
| 5.18.1 | Control signals for multi-switches | 48 |
| 5.18.2 | Amplitude frequency response flatness..... | 48 |
| 5.18.3 | Return loss | 48 |
| 5.18.4 | Through loss..... | 48 |
| 5.18.5 | Isolation..... | 48 |
| 5.18.6 | Crosstalk attenuation..... | 48 |
| 5.18.7 | Satellite IF to terrestrial signal isolation | 48 |

| | |
|--|----|
| 5.19 Immunity to surge voltages..... | 49 |
| 5.19.1 Degrees of testing levels | 49 |
| 5.19.2 Recommendation of testing level degree | 49 |
| Annex A (informative) Derivation of non-linear distortion..... | 50 |
| Annex B (normative) Test carriers, levels and intermodulation products..... | 52 |
| Annex C (normative) Checks on test equipment..... | 54 |
| Annex D (informative) Test frequency plan for composite triple beat (CTB), composite second order (CSO) and crossmodulation (XM) measurement | 55 |
| Annex E (informative) Measurement errors which occur due to mismatched equipment | 56 |
| Annex F (informative) Examples of signals, methods of measurement and network design for return paths..... | 57 |
| Bibliography..... | 64 |
| | |
| Figure 1 – Maximum error a for measurement of return loss using VSWR-bridge with directivity $D = 46$ dB and 26 dB test port return loss..... | 18 |
| Figure 2 – Measurement of return loss..... | 19 |
| Figure 3 – Basic arrangement of test equipment for evaluation of the ratio of signal to intermodulation product | 21 |
| Figure 4 – Connection of test equipment for the measurement of non-linear distortion by composite beat..... | 24 |
| Figure 5 – Connection of test equipment for the measurement of composite crossmodulation..... | 28 |
| Figure 6 – Carrier/hum ratio | 30 |
| Figure 7 – Test set-up for local-powered objects | 31 |
| Figure 8 – Test set-up for remote-powered objects | 31 |
| Figure 9 – Oscilloscope display..... | 32 |
| Figure 10 – Time constant T_C | 33 |
| Figure 11 – Measurement of AGC step response | 34 |
| Figure 12 – Measurement of noise figure | 35 |
| Figure 13 – Measurement of crosstalk attenuation for loop trough ports of multi-switches..... | 37 |
| Figure 14 – Characteristic of the noise filter..... | 39 |
| Figure 15 – Test setup for the non-linearity measurement..... | 39 |
| Figure 16 – Presentation of the result of $CINR$ | 41 |
| Figure 17 – Measurement set-up for surge immunity test | 42 |
| Figure B.1 – An example showing products formed when $2f_a > f_b$ | 52 |
| Figure B.2 – An example showing products formed when $2f_a < f_b$ | 53 |
| Figure B.3 – Products of the form $f_a \pm f_b \pm f_c$ | 53 |
| Figure E.1 – Error concerning return loss measurement..... | 56 |
| Figure E.2 – Maximum ripple | 56 |
| Figure F.1 – Spectrum of a QPSK-modulated signal | 57 |
| Figure F.2 – Measurement of non-linearity using wideband noise..... | 59 |
| Figure F.3 – Network used in the design example | 60 |
| Figure F.4 – A test result measured from a real 20 dB return amplifier | 61 |
| Figure F.5 – The $CINR$ curve of one amplifier is modified to represent the $CINR$ of the whole coaxial section of the network..... | 62 |

| | |
|--|----|
| Figure F.6 – The <i>CINR</i> of an optical link as a function of <i>OMI</i> , example..... | 63 |
| Table 1 – Correction factors where the modulation used is other than 100 % | 26 |
| Table 2 – Notch filter frequencies | 39 |
| Table 3 – Return loss requirements for all equipment..... | 44 |
| Table 4 – Parameters of surge voltages for different degrees of testing levels | 49 |
| Table 5 – Recommendations for degree of testing levels | 49 |
| Table D.1 – Frequency allocation plan | 55 |
| Table F.1 – Application of methods of measurement in IEC 60728-3 for return path equipment..... | 58 |
| Table F.2 – Application of methods of measurement in IEC 60728-6 for return path equipment..... | 58 |

INTERNATIONAL ELECTROTECHNICAL COMMISSION

CABLE NETWORKS FOR TELEVISION SIGNALS, SOUND SIGNALS AND INTERACTIVE SERVICES –

Part 3: Active wideband equipment for cable networks

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60728-3 has been prepared by technical area 5: Cable networks for television signals, sound signals and interactive services, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

This fourth edition cancels and replaces the third edition published in 2005 of which it constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- extension of upper frequency range limit for cable network equipment from 862 MHz to 1 000 MHz;
- method of measurement and requirements for immunity to surge voltages;
- extension of scope to equipment using symmetrical ports;
- additional normative references;

I.S. EN 60728-3:2011

60728-3 © IEC:2010(E)

– 7 –

- additional terms and definitions and abbreviations.

The text of this standard is based on the following documents:

| FDIS | Report on voting |
|---------------|------------------|
| 100/1746/FDIS | 100/1766/RVD |

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The list of all the parts of the IEC 60728 series, under the general title *Cable networks for television signals, sound signals and interactive services*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

Standards of the IEC 60728 series deal with cable networks including equipment and associated methods of measurement for headend reception, processing and distribution of television signals, sound signals and their associated data signals and for processing, interfacing and transmitting all kinds of signals for interactive services using all applicable transmission media.

This includes

- CATV¹-networks;
- MATV-networks and SMATV-networks;
- individual receiving networks;

and all kinds of equipment, systems and installations installed in such networks.

For active equipment with balanced RF signal ports this standard applies to those ports which carry RF broadband signals for services as described in the scope of this standard.

The extent of this standardization work is from the antennas and/or special signal source inputs to the headend or other interface points to the network up to the terminal input.

The standardization of any user terminals (i.e., tuners, receivers, decoders, multimedia terminals, etc.) as well as of any coaxial, balanced and optical cables and accessories thereof is excluded.

¹ This word encompasses the HFC (Hybrid Fibre Cable) networks used nowadays to provide telecommunications services, voice, data, audio and video both broadcast and narrowcast.

CABLE NETWORKS FOR TELEVISION SIGNALS, SOUND SIGNALS AND INTERACTIVE SERVICES –

Part 3: Active wideband equipment for cable networks

1 Scope

This part of IEC 60728 lays down the measuring methods, performance requirements and data publication requirements for active wideband equipment of cable networks for television signals, sound signals and interactive services.

This standard

- applies to all broadband amplifiers used in cable networks;
- covers the frequency range 5 MHz to 3 000 MHz;

NOTE The upper limit of 3 000 MHz is an example, but not a strict value. The frequency range, or ranges, over which the equipment is specified, should be published.

- applies to one-way and two-way equipment;
- lays down the basic methods of measurement of the operational characteristics of the active equipment in order to assess the performance of this equipment;
- identifies the performance specifications to be published by the manufacturers;
- states the minimum performance requirements of certain parameters.

Amplifiers are divided into the following two quality levels:

Grade 1: amplifiers typically intended to be cascaded;

Grade 2: amplifiers for use typically within an apartment block, or within a single residence, to feed a few outlets.

Practical experience has shown that these types meet most of the technical requirements necessary for supplying a minimum signal quality to the subscribers. This classification is not a requirement but is provided to users and manufacturers for information about minimum quality criteria of the material required to install networks of different sizes. The system operator has to select appropriate material to meet the minimum signal quality at the subscriber's outlet, and to optimise cost/performance, taking into account the size of the network and local circumstances.

All requirements and published data are understood as guaranteed values within the specified frequency range and in well-matched conditions.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60065, *Audio, video and similar electronic apparatus – Safety requirements*

IEC 60068-1:1998, *Environmental testing – Part 1: General and guidance*

IEC 60068-2-1, *Environmental testing – Part 2-1: Tests – Tests A: Cold*

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

-
- [Looking for additional Standards? Visit Intertek Inform Infostore](#)
 - [Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation](#)
-