This is a free page sample. Access the full version online.



Irish Standard Recommendation S.R. CLC/TR 50609:2014

Technical Guidelines for Radial HVDC Networks

© CENELEC 2014 No copying without NSAI permission except as permitted by copyright law.

S.R. CLC/TR 50609:2014

Incorporating amendments/corrigenda/National Annexes issued since publication:

The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:

I.S. xxx: Irish Standard – national specification based on the consensus of an expert panel and subject to public consultation.

S.R. xxx: Standard Recommendation — recommendation based on the consensus of an expert panel and subject to public consultation.

SWIFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.

This document replaces/revises/consolidates the NSAI adoption of the document(s) indicated on the CEN/CENELEC cover/Foreword and the following National document(s):

NOTE: The date of any NSAI previous adoption may not match the date of its original CEN/CENELEC document.

This document is based on: CLC/TR 50609:2014 *Published:* 2014-02-28

This document was published		ICS number:	
under the authority of the NSAI and comes into effect on:			29.240.01
2014-03-11			
		NOTE: If bla	ank see CEN/CENELEC cover page
NSAI	T +353 1	807 3800	Sales:
1 Swift Square,	F +353 1	807 3838	T +353 1 857 6730
Northwood, Santry	E standa	Irds@nsai.ie	F +353 1 857 6729
Dublin 9	W NSAI.i	e	W standards.ie

Údarás um Chaighdeáin Náisiúnta na hÉireann

This is a free page sample. Access the full version online. S.R. CLC/TR 50609:2014

TECHNICAL REPORT RAPPORT TECHNIQUE TECHNISCHER BERICHT

CLC/TR 50609

February 2014

ICS 29.240.01

English version

Technical Guidelines for Radial HVDC Networks

Directives techniques pour les réseaux HVDC radiaux Technischer Leitfaden für radiale HGÜ-Netze

This Technical Report was approved by CENELEC on 2013-12-09.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B - 1000 Brussels

© 2014 CENELEC - All rights of exploitation in any form and by any means reserved worldwide for CENELEC members.

Ref. No. CLC/TR 50609:2014 E

Contents

Page

Fe	orew	ord	
0		Int	roduction
	0.1	The	European HVDC Grid Study Group 8
	0.2 Technology		nnology9
	0.:	2.1	Converters
	0.:	2.2	DC Circuit9
	0.:	2.3	Technological Focus of the European HVDC Grid Study Group
1		Sc	ope12
2		Te	rminology and abbreviations
	2.1	Gen	eral 12
	2.2	Tern	ninology and abbreviations for HVDC Grid Systems used in this report
	2.3	Prop	bosed Terminology by the Study Group13
3		Ту	pical Applications of HVDC Grids14
	3.1	The	Development of HVDC Grid Systems 14
	3.2 Planning Criteria for Topologies		ning Criteria for Topologies15
	3.:	2.1	General15
	3.	2.2	Power Transfer Requirements 16
	3.	2.3	Reliability 17
	3.:	2.4	Losses
	3.:	2.5	Future Expansions
	3.3	Tech	nnical Requirements
	3.	3.1	General 21
	3.	3.2	Converter Functionality

	3.3.3	Start/stop Behaviour of Individual Converter Stations	23
	3.3.4	Network Behaviour during Faults	24
	3.3.5	DC-AC Interface Requirements	25
	3.3.6	The Role of Communication	26
	3.4 Тур	ical Applications – Relevant Topologies	27
	3.4.1	General	27
	3.4.2	Radial Topology	27
	3.4.3	Meshed Topology	29
	3.4.4	HVDC Grid Systems Connecting Offshore Wind Power Plants	29
	3.4.5	Connection of a wind power plant to an existing HVDC VSC link	30
4	Pr	inciples of DC Load Flow	31
	4.1 Ger	neral	31
	4.2 Stru	Icture of Load Flow Controls	31
	4.2.1	General	31
	4.2.2	Converter Station Controller	31
	4.2.3	HVDC Grid Controller	32
	4.3 Con	overter Station Control Functions	34
	4.3.1	General	34
	4.3.2	DC Voltage (U _{DC}) Stations	34
	4.3.3	Active Power (P _{DC}) and Frequency (f) Controlling Stations	34
	4.4 Para	alleling Transmission Systems	35
	4.4.1	General	35
	4.4.2	Paralleling on AC and DC side	35
	4.4.3	Paralleling on the AC side	35
	4.4.4	Steady-State Loadflow in Hybrid AC/DC Networks	36

4.5	Load	d Flow Control	38
4.	5.1	DC Voltage Operating Range	38
4.	5.2	Static and Dynamic System Stability	39
4.	5.3	Step response	39
4.6	HVD	C Grid Control Concepts	40
4.	6.1	General	40
4.	6.2	Voltage-Power Droop Together with Dead Band	45
4.	6.3	Voltage-Current Droop	48
4.	6.4	Voltage-Power Droop — Control of the HVDC Grid Voltage	54
4.7	Ben	chmark Simulations of Control Concepts	57
4.	7.1	Case Study	57
4.	7.2	Results	58
4.	7.3	Conclusions	60
4.	7.4	Interoperability	61
5	Sh	ort-Circuit Currents and Earthing	61
5.1	Gen	eral	61
5.2	Calc	culation of Short-Circuit Currents in HVDC Grid Systems	61
5.3	Netv	work Topologies and their Influence on Short-Circuit Currents	63
5.	3.1	Influence of DC Network Structure	63
5.	3.2	Influence of Line Discharge	66
5.	3.3	Influence of Capacitors	67
5.	3.4	Contribution of Converter Stations	69
5.	3.5	Methods of Earthing	72
5.4	Seco	ondary Conditions for Calculating the Maximum/Minimum Short-Circuit Current	73
5.5	Calc	culation of the Total Short-Circuit Current (Super Position Method)	74

	5.6	Redu	uction of Short-Circuit Currents	75
6		Prir	nciples of HVDC Grid Protection	76
	6.1	Gene	eral	76
	6.2	HVD	C Grid System	77
	6.3	AC/D	OC Converter	78
	6.3	3.1	General	78
	6.3	3.2	DC System	79
	6.3	3.3	HVDC Switchyard	80
	6.3	3.4	HVDC System without Fast Dynamic Isolation	80
	6.3	3.5	HVDC System with Fast Dynamic Isolation	80
	6.4	DC P	Protection	81
	6.4	4.1	General	81
	6.4	4.2	DC Converter Protections	81
	6.4	4.3	Protective Shut Down of a Converter	83
	6.4	4.4	DC System Protections	84
	6.4	4.5	DC Equipment Protections	84
	6.5	Clea	rance of Earth Faults	84
	6.	5.1	Clearance of a DC Pole-to-Earth Fault	84
	6.	5.2	Clearance of a Pole-to Pole Short Circuit	85
	6.	5.3	Clearance of a Converter side AC Phase-to-Earth Fault	85
7		Fur	nctional Specifications	85
	7.1	Gene	eral	85
	7.2	AC/D	OC Converter Stations	86
	7.2	2.1	DC System Characteristics	86
	7.2	2.2	Operational Modes	89
	7.2	2.3	Testing and Commissioning	95

7.3 H	IVDC breaker)6
7.3.1	1 System Requirements	96
7.3.2	2 System Functions	96
7.3.3	3 Interfaces and Overall Architecture	96
7.3.4	4 Service Requirements	96
7.3.5	5 Technical System Requirements	96
Annex A	(informative) HVDC – Grid Control Study	9
Annex B	(informative) Fault Behaviour of Full Bridge Type MMC10)6
B.1	Introduction10)6
B.2	Test Results)6
B.3	DC to DC Terminal Faults10)6
B.4	DC Terminal to Ground Faults10)7
B.5	Conclusion10)7
Bibliogra	aphy11	9

Foreword

This document (CLC/TR 50609:2014) has been prepared by CLC/TC 8X "System aspects of electrical energy supply".

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a mandate given to CENELEC by the European Commission and the European Free Trade Association.

This document was already sent out within CLC/TC 8X for comments and the comments received were discussed within CLC/TC 8X/WG 06 and were incorporated in the current document as far as appropriate.

0 Introduction

0.1 The European HVDC Grid Study Group

Existing power systems in Europe have been developing for more than 100 years to transmit the power, generated mainly by fossil and nuclear power plants to the loads. Climate change, limited fossil resources and concerns over the security of nuclear power are drivers for an increased utilization of renewable sources, such as wind and solar, to realize a sustainable energy supply. According to the geological conditions, the location of large scale renewable energy sources is different to the location of existing conventional power plants and imposes new challenges for the electric power transmission networks, such as extended transmission capacity requirements over long distances, load flow control and system stability. The excellent bulk power long distance transmission capabilities, low transmission technology for mastering these challenges, in particular for connection of offshore wind power plants to the onshore transmission systems.

While the power system reinforcement is already underway by a number of new point-to-point HVDC interconnections, the advantages offered by multiterminal HVDC systems and HVDC grids become more and more attractive. Examples are grid access projects connecting various wind power plants or combining wind plants with point-to-point transmission, e.g. in the North and Baltic Seas. Multiterminal projects are already in execution and there is planning for pan-European HVDC grids. In this document, multiterminal HVDC systems and HVDC grids are referred to as HVDC Grid Systems.

To become reality, HVDC Grid Systems need, in addition to the necessary political framework for cross country system design, construction and operation, competitive supply chains of equipment capable of operating together as an integrated system. This marks a significant change in the HVDC technology market. While today - with very few exceptions – a HVDC transmission system has been provided by a single manufacturer, future HVDC Grid Systems will be built step by step composed of converters and HVDC substations supplied by different manufacturers. Interoperability will thus become a fundamental requirement for future HVDC technology.

Common understanding of basic operating and design principles of HVDC Grid Systems is seen as a first step towards multi vendor systems, as it will help the development for the next round of European multiterminal projects. Furthermore, it will prepare the ground for more detailed standardization work.

Based on an initiative by the DKE German Commission for Electrical, Electronic and Information Technologies, the European HVDC Grid Study Group has been founded in September 2010 to develop "Technical Guidelines for first HVDC Grids". The Study Group has the following objectives:

- to describe basic principles of HVDC grids with the focus on near term applications;
- to develop functional specifications of the main equipment and HVDC grid controllers;
- to develop "New Work Item Proposals" to be offered to CENELEC for starting standardization work.

CIGRÉ SC B4, CENELEC TC8x and ENTSO-E and "Friends of the Supergrid" are involved at an informative level with the results of the work.

Members affiliated with the following companies and organizations have been actively contributing to the results of the Study Group achieved so far: 50 Hz Transmission, ABB, ALSTOM, Amprion, DKE,

TransnetBW, Energinet.dk, ETH Zurich, National Grid, Nexans, Prysmian, SEK, Siemens, TenneT and TU Darmstadt.

As a starting point the Study Group has been investigating typical applications and performance requirements of HVDC Grid Systems. This information helps elaborating the basic principles of HVDC networks, which are described in the following clauses:

- Clause 3, Typical Applications of HVDC Grids;
- Clause 4, Principles of DC Load Flow;
- Clause 5, Short-Circuit Currents and Earthing;
- Clause 6, Principles of HVDC Grid Protection.

From the technical principles described, functional specifications for the main equipment of HVDC networks are derived and summarized in Clause 7.

0.2 Technology

0.2.1 Converters

HVDC transmission started more than 60 years ago. Today, the installed HVDC transmission capacity exceeds 200 GW worldwide. The vast majority of the existing HVDC links are based on so-called Line-Commutated-Converters (LCC). LCC today are built from Thyristors. The power exchange of such converters is determined by controlling the point–on-wave of valve turn-on, while the turn-off occurs due to the natural zero crossing of valve current forced by the AC network voltage. That is why LCC rely on relatively strong AC systems to provide conversion from AC to DC and vice versa.

With so-called Voltage Sourced Converters (VSC), a different type of converters has been introduced to HVDC transmission slightly more than a decade ago. VSCs today utilize Insulated Gate Bipolar Transistors (IGBT) as the main switching elements. IGBTs have controlled turn-on as well as turn-off capability making the VSCs capable of operating under weak AC system conditions or supplying power systems where there is no other voltage source, also referred to as passive networks.

The evolution of VSC transmission was started with so-called Two-Level converters at the end of the 1990s and has commenced to Three Level Converters and further to Modular Multilevel Converters (MMC) which have made their break-through in the mid to late 2000s. All MMC type converters apply the same principle of connecting a number of identical converter building blocks in series. However, at the present time there are basically two types of such building blocks: referred to as Half-Bridge (HB) and Full-Bridge (FB) modules.

Other converter equipment which have been proposed for HVDC Grid applications, such as DC/DC converters, load flow controllers, etc. are not discussed in this document.

0.2.2 DC Circuit

Similar to AC networks, HVDC transmission systems can be distinguished by their network topologies as radial and/or meshed networks and with respect to earthing in effectively grounded and isolated systems. Both aspects influence the design criteria and the behaviour of the HVDC system.

- Radial and Meshed Topologies:

In radial systems, there is not more than one connection between two arbitrary nodes of the network. The DC voltages of the converter stations connected to each end of a line solely determine the power flow through that line, for example in Figure 1-1, station C is radially connected with station D.

In meshed systems, at least two converter stations have more than one connecting path. Without any additional measures the current through a line will then be determined by the DC voltages of the converter stations as well as the resistances of the parallel connections. In Figure 1-1, the DC circuit connecting stations A, B and C forms a meshed system while C and D is a radial connection. A HVDC Grid System having a meshed topology can be operated as a radial system if parallel connections are opened by disconnectors or breakers.





<u>Earthing:</u>

DC circuits can be effectively grounded if one DC pole is connected to earth through a low ohmic branch. Such systems are also referred to as asymmetrical Monopoles or just "Monopoles". Two Monopoles of opposite DC voltage polarity are often combined into so-called bipolar systems or just "Bipoles".

Isolated DC circuits do not have a low ohmic connection to ground on the DC side. These configurations are also referred to as "Symmetrical Monopoles".

0.2.3 Technological Focus of the European HVDC Grid Study Group

Various technologies are available for building HVDC Grid Systems. Some of them have already been used in commercial projects; others are in the demonstration phase or are in an early stage of discussion. This applies to the converter technology as well as the topologies of connecting them into a HVDC Grid System.

Serving the near term applications, the Study Group decided to focus its scope of work on radial HVDC network structures as well as pure VSC based solutions. Both grounded and ungrounded DC circuits are considered.

The integration of HVDC Grid Systems is seen as an important part of developing future electric power systems. The Study Group bases its work on typical requirements applied to state of the art HVDC converter stations today and investigates aspects that are specifically related to the design and operation of converter stations and DC circuits. The requirements from the AC systems as known today are included. Secondary effects associated with changing the AC systems, e.g. the replacement of rotating machines by power electronic devices, are not within the scope of the Study Group.

The Study Group report summarizes the selected results of work and gives recommendations for the next steps towards preparing the ground for standardization of HVDC multiterminal systems and HVDC Grid Systems.

The interface requirements and functional specifications given in this document are intended to support the specification and purchase of multi vendor multiterminal HVDC Grid Systems.

1 Scope

This Technical Report applies to HVDC Systems having more than two converter stations connected to a common DC network, also referred to as HVDC Grid Systems. Serving the near term applications, this report describes radial HVDC network structures as well as pure VSC based solutions. Both grounded and ungrounded DC circuits are considered.

Based on typical requirements applied to state of the art HVDC converter stations today this report addresses aspects that are specifically related to the design and operation of converter stations and DC circuits in HVDC Grid Systems. The requirements from the AC systems as known today are included. Secondary effects associated with changing the AC systems, e.g. the replacement of rotating machines by power electronic devices, are not within the scope of the present report.

The report summarizes applications and concepts of HVDC Grid Systems with the purpose of preparing the ground for standardization of such systems.

The interface requirements and functional specifications given in this document are intended to support the specification and purchase of multi-vendor multiterminal HVDC Grid Systems.

2 Terminology and abbreviations

2.1 General

In the work undertaken here it has been identified that a common list of terminology and abbreviations used specifically to describe HVDC Grids should be established.

The International Electrotechnical Commission (IEC) standard EN 60633 [1] describes General Terminology for HVDC Transmission and is the reference for common terms and abbreviations. Furthermore EN 62501 [2] describes electrical testing of VSC. A new proposed work item in IEC is to develop terminology for VSC HVDC systems. In addition CIGRÉ has published a brochure 269 on basic operational principles of VSC-HVDC [3]. Specific terms required for components and methods for multiterminal HVDC Transmission, e.g. HVDC breakers and control modes, are described here.

The Study Group has established information exchange established with the ongoing CIGRÉ B4.52 feasibility study on DC Grids. Also in the CIGRÉ work, new terms used to describe phenomena and components in DC grids are used. The terminology used in this report corresponds to the terminology used in the CIGRÉ working group.

2.2 Terminology and abbreviations for HVDC Grid Systems used in this report

- AC Alternating Current
- DC Direct Current
- ENTSO-E European Network of Transmission System Operators for Electricity
- FB Full Bridge
- GW Giga Watts



This is a free preview. Purchase the entire publication at the link below:

Product Page

S Looking for additional Standards? Visit Intertek Inform Infostore

> Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation