

Irish Standard I.S. EN 16480:2016

Pumps - Minimum required efficiency of rotodynamic water pumps

 $\ensuremath{\mathbb C}$ CEN 2016 $\hfill No copying without NSAI permission except as permitted by copyright law.$

I.S. EN 16480:2016

Incorporating amendments/corrigenda/National Annexes issued since publication:

The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:

I.S. xxx: Irish Standard – national specification based on the consensus of an expert panel and subject to public consultation.

S.R. xxx: Standard Recommendation — recommendation based on the consensus of an expert panel and subject to public consultation.

SWiFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.

This document replaces/revises/consolidates the NSAI adoption of the document(s) indicated on the CEN/CENELEC cover/Foreword and the following National document(s):

NOTE: The date of any NSAI previous adoption may not match the date of its original CEN/CENELEC document.

This document is based on: EN 16480:2016

Published: 2016-05-18

This document was published under the authority of the NSAI and comes into effect on:

2016-06-05

ICS number:

23.080

NOTE: If blank see CEN/CENELEC cover page

NSAI	T +353 1 807 3800	Sales:
1 Swift Square,	F +353 1 807 3838	T +353 1 857 6730
Northwood, Santry	E standards@nsai.ie	F +353 1 857 6729
Dublin 9	W NSAI.ie	W standards.ie

Údarás um Chaighdeáin Náisiúnta na hÉireann

National Foreword

I.S. EN 16480:2016 is the adopted Irish version of the European Document EN 16480:2016, Pumps - Minimum required efficiency of rotodynamic water pumps

This document does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with this document does not of itself confer immunity from legal obligations.

In line with international standards practice the decimal point is shown as a comma (,) throughout this document.

This is a free page sample. Access the full version online.

This page is intentionally left blank

This is a free page sample. Access the full version online. I.S. EN 16480:2016

EUROPEAN STANDARD NORME EUROPÉENNE

EN 16480

EUROPÄISCHE NORM

May 2016

ICS 23.080

English Version

Pumps - Minimum required efficiency of rotodynamic water pumps

Pompes - Rendement minimum requis des pompes à eau rotodynamiques Pumpen - Geforderte Mindesteffizienz bei Kreiselpumpen für Wasser

This European Standard was approved by CEN on 4 March 2016.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

© 2016 CEN All rights of exploitation in any form and by any means reserved worldwide for CEN national Members.

Ref. No. EN 16480:2016 E

Contents

Europ	European foreword		
Introduction		5	
1	Scope	7	
2	Normative references	8	
3 3.1 3.2 3.3 3.4	Terms and definitions General List of quantities with definitions Lists of basic letters and subscripts General definitions	8 8 8 10 12	
4 4.1 4.2 4.3 4.4	Minimum Required Efficiencies and Minimum Efficiency Index The concept of "house of efficiency" Mathematical representation of minimum required efficiency Minimum efficiency at part load and overload Minimum Efficiency Index	14 14 15 16 17	
5 5.1 5.2 5.3 5.4 5.5	Determination of the Efficiency of a Test Pump General Test Procedures Test conditions Measuring uncertainties Evaluation of test data	20 20 20 21 22 24	
6 6.1 6.2	Proving the Minimum Efficiency Index of a pump size General remarks Determination of the Minimum Efficiency Index of a pump size	29 29 30	
7 7.1 7.2	Verification of the Minimum Efficiency Index for a pump size General remarks Procedure and decision	31 31 31	
Annex A (normative) Pump types in scope			
Annex	Annex B (informative) General remarks on the efficiency of rotodynamic pumps		
Annex	C (informative) Mean Values of a Size Relevant for its Minimum Efficiency Index	39	
Annex	D (informative) Methods recommended for manufacturers to determine the mean values of hydraulic quantities of a size relevant for MEI	44	
D.1	General remarks	44	
D.2	Determination of the mean efficiency of a pump size from a test on one single test pump	44	
D.3	Determination of the mean efficiency of a pump size from a sample of M test pumps	46	
Annex	Annex E (informative) Numerical example		
Annex	Annex F (informative) Application of mathematical statistics on tests		
F.1	Purposes of applying statistics in the frame of qualification and verification	54	
F.2	Confidence interval	55	

F.3	Law of error propagation	57
F.4	Numerical example	57
Annex	G (informative) Measurement uncertainties	64
G.1	General remarks	64
G.2	Determination of the overall measurement uncertainty of efficiency	66
Annex	H (informative) Explanations concerning the methodology of the verification procedure and the probability of the results	68
Annex	I (informative) Reporting of Test Results	71
I.1	Test Report Requirements	71
I.2	Pump test sheet	71
Annex	ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2009/125/EC, establishing a framework for the setting of ecodesign requirements of energy related products and implemented by the European Commission Regulation (EU) No. 547/2012	73
Bibliog	graphy	74

European foreword

This document (EN 16480:2016) has been prepared by Technical Committee CEN/TC 197 "Pumps - Minimum required efficiency of rotodynamic water pumps", the secretariat of which is held by AFNOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by November 2016, and conflicting national standards shall be withdrawn at the latest by November 2016.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive 2009/125/EC.

For relationship with EU Directive 2009/125/EC, see informative Annex ZA, which is an integral part of this document.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Introduction

Purpose and content of the standard

The water pumps within the scope of this European Standard are typically produced and sold by pump manufacturers as series of large to very large numbers. The performance characteristics of pumps of one size produced by a manufacturer show some scatter caused by manufacturing tolerances, but are described by mean values and curves which represent that size.

The total consumption of electric energy by water pumps installed in applications within the scope of this European Standard depends on the total number of installed pumps of each size and on its mean efficiency. The quality of a size in respect to its mean efficiency is quantitatively described by the Minimum Efficiency Index (MEI) which is defined and used in this standard. To achieve a certain value of the Minimum Efficiency Index (MEI), a corresponding minimum value of the mean efficiency of a size is required.

This European Standard defines – for each pump type and size within the scope of the standard - the minimum required value of efficiency depending on the value of the Minimum Efficiency Index (MEI). Also, this standard prescribes how the value of the Minimum Efficiency Index (MEI) of a pump size indicated by the manufacturer can be verified by an independent institution (e.g. in the frame of market surveillance). For the manufacturer of the pump size it is generally left free how to prove the indicated value of the Minimum Efficiency Index (MEI) of a size. Nevertheless, this standard describes also a method to prove by the manufacturer that the mean values of efficiency meet the requirements for indicating a certain value of the Minimum Efficiency Index (MEI).

Normally, the qualification of a pump size for a certain MEI value done by the manufacturer will be based on tests and evaluations made on a sample of pumps of this size. It is essential that tests and evaluations carried out for the purpose of qualifying the corresponding size fulfil certain requirements:

- From the tests on the sample pumps, it becomes possible to predict for the corresponding size the confidence intervals within which the true mean values of efficiencies which are relevant for the qualification are enclosed with a sufficiently high probability. Only in that way, the qualification of the size in respect to a required and/or indicated value of Minimum Efficiency Index (MEI) will make sure that the aspired effect of energy saving will be reached.
- If a pump size has been qualified according to the criteria described in this European Standard, every test on one or more test pump(s) of the same size (with a full impeller diameter) which is carried out in the frame of a verification procedure shall result with a very high probability in a confirmation of the qualification.

Caused by technical alignment procedures of the single pump components, e.g. bearings or shaft seals, the performance of the pump is gained after a certain running-in time.

Ways to prove and to verify the Minimum Efficiency Index (MEI) of a pump size

This European Standard describes different ways how manufacturers can achieve the qualification of a pump size for a certain value of the Minimum Efficiency Index (MEI) and how this qualification can be verified by an independent institution.

For the <u>manufacturer</u>, it is generally left free to choose and apply appropriate methods to prove that the mean efficiency values of a size are at least equal to or higher than particular threshold values of efficiency. These particular threshold values of efficiency are related to the value of the Minimum Efficiency Index (MEI) to be indicated for the size. The way to determine these values of efficiency is described in this standard. If the way chosen by the manufacturer to prove the MEI value of a size deviates from the way mentioned in the next paragraph, the manufacturer has to document all tests, evaluations and/or calculations which are carried out and the methods which are applied to prove the justification of the indicated MEI value.

If the manufacturer decides to determine the mean performance values of the size by one of the methods described in Annex D of this standard, he has to carry out tests according to the requirements given in Annex C of this standard and evaluations as described in Annex C of this standard and to prove – as described in Clause 7 of this standard – that the criteria for the achievement of a certain value of the Minimum Efficiency Index (MEI) of the size are fulfilled. The test conditions, the results of test evaluation and the fulfilment of the criteria are documented and stored. The time period to keep documentation available for the authorities to prove conformity is fixed by the legal text.

The independent institution carries out tests on pumps of the size in question according to the requirements given in 5.2 to 5.4 of this standard as well as evaluations as described in 5.5 of this standard and applies the methodology and procedure described in Clause 4 of this standard.

For an <u>independent institution</u>, two ways are possible and specified by this standard to verify the value of Minimum Efficiency Index (MEI) indicated by the manufacturer:

- a) If the documentation of the qualification is presented by the manufacturer to the independent institution on request, the procedure of verification executed by the independent institution is based on the documentation of tests and evaluations done and documented by the manufacturer. In this case, the documentation will be checked by the independent institution in respect to being in accordance with requirements and criteria given in this standard.
- b) If no documentation is presented by the manufacturer on request or if the documentation presented by the manufacturer on request is not accepted as proof of the indicated value of MEI, the independent institution carries out tests on pumps of the size in question according to the requirements given in Annex C of this standard as well as evaluations as described in 5.5 of this standard and applies the methodology and procedure described in Clause 4 of this standard.

Relevance of Sections of this standard for manufacturers or independent institutions

Clause 4 describes nominal values of minimum required efficiency for a certain value of the Minimum Efficiency Index (MEI) and is generally relevant when applying this standard.

Clause 5 specifies test procedures, test conditions and evaluations and has to be applied

- by a manufacturer in the case that he decides to determine mean values of a size by tests on sample pumps of this size (e.g. by methods described in Annex D),
- by an independent institution in the case that the Minimum Efficiency Index (MEI) of a pump size shall be verified by the procedure described in Clause 7.

Clause 6 describes the procedure to be applied by a manufacturer in order to determine particular threshold values of efficiency for a certain value of the Minimum Efficiency Index (MEI) of a size and to prove the justification of this MEI value by the fulfilment of criteria for the mean efficiency values.

Clause 7 describes the methodology and procedure to be applied by an independent institution in the case that the Minimum Efficiency Index (MEI) of a size indicated by the manufacturer shall be verified by third party tests on pumps of this size.

Annex C is concerned with mean values of a pump size which are relevant for manufacturers to prove that a pump size achieves a certain value of the Minimum Efficiency Index (MEI).



This is a free preview. Purchase the entire publication at the link below:

Product Page

S Looking for additional Standards? Visit Intertek Inform Infostore

> Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation