

Irish Standard I.S.EN ISO 11562:1998

Geometrical product specifications (GPS) -Surface texture : Profile method -Metrological characteristics of phase correct filters (ISO 11562 : 1996)

© NSAI 1997

No copying without NSAI permission except as permitted by copyright law.

Incorporating amendments/o	corrigenda issued since pu	ıblication:		
The National Standards Authorit documents:	y of Ireland (NSAI) produc	es the following categ	gories of formal	
.S. xxx: Irish Standard - na subject to public consultation.	ational specification based	d on the consensus of	an expert panel and	
5.R. xxx: Standard Recommoanel and subject to public consu	endation - recommendati ıltation.	on based on the conse	ensus of an expert	
SWiFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.				
This document replaces:				
This document is based on: EN ISO 11562:1997	<i>Published:</i> 17 December, 1997			
This document was publishe under the authority of the N and comes into effect on: 15 May, 1998			ICS number: 17.040.20	
<b>NSAI</b> 1 Swift Square, Northwood, Santry Dublin 9	T +353 1 807 3800 F +353 1 807 3838 E standards@nsai.ie W NSAI.ie	<b>Sales:</b> T +353 1 857 6730 F +353 1 857 6729 W standards.ie		
Údarás um Chaighdeáin Náisiúnta na hÉireann				

### EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

EN ISO 11562:1997/AC

October 2008 Octobre 2008 Oktober 2008

ICS 17.040.20

English version Version Française Deutsche Fassung

Geometrical product specifications (GPS) - Surface texture: Profile method - Metrological characteristics of phase correct filters (ISO 11562:1996/Cor 1:1998)

Spécification géométrique des produits (GPS) - Etat de surface: Méthode du profil - Caractéristiques métrologiques des filtres à phase correcte (ISO 11562:1996/Cor 1:1998)

Geometrische Produktspezifikationen (GPS) - Oberflächenbeschaffenheit: Tastschnittverfahren - Meßtechnische Eigenschaften von phasenkorrekten Filtern (ISO 11562:1996/Cor 1:1998)

This corrigendum becomes effective on 15 October 2008 for incorporation in the three official language versions of the EN.

Ce corrigendum prendra effet le 15 octobre 2008 pour incorporation dans les trois versions linguistiques officielles de la EN.

Die Berichtigung tritt am 15.Oktober 2008 zur Einarbeitung in die drei offiziellen Sprachfassungen der EN in Kraft.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

EN ISO 11562:1997/AC:2008 (E)

### **Endorsement notice**

The text of ISO 11562:1996/Cor.1:1998 has been approved by CEN as a European Corrigendum without any modification.



### INTERNATIONALISTANDARD ISO 11562:1996 TECHNICAL CORRIGENDUM 1

Published 1998-06-15

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

## Geometrical Product Specifications (GPS) — Surface texture: Profile method — Metrological characteristics of phase correct filters

**TECHNICAL CORRIGENDUM 1** 

Spécification géométrique des produit	s (GPS) — État de surface	e: Méthode du profil —	Caractéristiques
métrologiques des filtres à phase corre	ecte		

RECTIFICATIF TECHNIQUE 1

Technical Corrigendum 1 to International Standard ISO 11562:1996 was prepared by Technical Committee ISO/TC 213, *Dimensional and geometrical product specifications and verification*.

Page 7

Figure B.1

Replace "Datum planes" with "Datums".

ICS 17.040.20

Ref. No. ISO 11562:1996/Cor.1:1998(E)

**Descriptors:** surface condition, surface waviness, roughness, roughness measurement, measuring instruments, profile meters, filters, metrological characteristics.

© ISO 1998

Printed in Switzerland

I.S. EN ISO 11562:1998

This page is intentionally left BLANK.

### EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

**EN ISO 11562** 

December 1997

ICS 17.040.20

Descriptors: see ISO document

#### **English version**

Geometrical product specifications (GPS) - Surface texture: Profile method - Metrological characteristics of phase correct filters (ISO 11562:1996)

Spécification géométrique des produits (GPS) - Etat de surface: Méthode du profil - Caractéristiques métrologiques des filtres à phase correcte (ISO 11562:1996)

Geometrische Produktspezifikationen (GPS) -Oberflächenbeschaffenheit: Tastschnittverfahren -Meßtechnische Eigenschaften von phasenkorrekten Filtern (ISO 11562:1996)

This European Standard was approved by CEN on 2 November 1997.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Central Secretariat: rue de Stassart, 36 B-1050 Brussels

I.S. EN ISO 11562:1998

This page is intentionally left BLANK.

## INTERNATIONAL STANDARD

ISO 11562

> First edition 1996-12-01

# Geometrical Product Specifications (GPS) — Surface texture: Profile method — Metrological characteristics of phase correct filters

Spécification géométrique des produits (GPS) — État de surface: Méthode du profil — Caractéristiques métrologiques des filtres à phase correcte



### **Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 11562 was prepared jointly by Technical Committees ISO/TC 57, Metrology and properties of surfaces, Subcommittee SC 1, Geometrical parameters — Instruments and procedures for measurement of surface roughness and waviness, ISO/TC 3, Limits and fits, and ISO/TC 10, Technical drawings, product definition and related documentation, Subcommittee SC 5, Dimensioning and tolerancing.

Annexes A, B and C of this International Standard are for information only.

© ISO 1996

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization Case Postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

ISO 11562:1996(E)

### Introduction

This International Standard is a Geometrical Product Specification (GPS) standard and is to be regarded as a *General GPS standard* (see ISO/TR 14638). It influences chain links 2 and 3 of the chains of standards for roughness profile and waviness profile and chain link 2 of the chain of standards for primary profile and is envisaged also to cover roundness and other form characteristics.

For more detailed information of the relation of this standard to other standards and the GPS matrix model, see annex B.

For digital instruments, the appropriate filter for surface profile information is a phase correct filter. The chosen weighting function, for the phase correct filter, is Gaussian with a 50 % transmission at the cut-off wavelength. This provides a transmission characteristic with a relatively sharp cut-off.

It is of importance that the transmission for the cut-off wavelength is 50 % since the short wave and long wave portions of the surface profile are separated and can be recombined without altering the surface profile.

I.S. EN ISO 11562:1998

This page intentionally left blank

## Geometrical Product Specifications (GPS) — Surface texture: Profile method — Metrological characteristics of phase correct filters

### 1 Scope

This International Standard specifies the metrological characteristics of phase correct filters for the measurement of surface pofiles.

In particular it specifies how to separate the long and short wave content of a surface profile.

### 2 Definitions

For the purposes of this International Standard, the following definitions apply.

- 2.1 profile filter: Filter which serapates profiles into longwave and shortwave components.
- **2.1.1 phase correct profile filter:** Profile filter which does not cause phase shifts which lead to asymmetrical profile distortions.
- **2.2 phase correct filter mean line (mean line):** Long wave profile component which is determined for any point of the profile by a weighted mean value derived from adjacent points.
- **2.3** transmission characteristic of a filter: Characteristic which indicates the amount by which the amplitude of a sinusoidal profile is attenuated as a function of its wavelength.
- **2.4 weighting function:** Function for calculating the mean line which indicates for each point the weight attached by the profile in the neighbourhood of that point.
- NOTE The transmission characteristic of the mean line is the Fourier transformation of the weighting function.
- **2.5 cut-off wavelength of the phase correct filter:** Wavelength of a sinusoidal profile of which 50 % of the amplitude is transmitted by the profile filter.
- NOTE Profile filters are identified by their cut-off wavelength value.



	This is a free preview.	Purchase the e	entire publication	at the link below:
--	-------------------------	----------------	--------------------	--------------------

**Product Page** 

- Dooking for additional Standards? Visit Intertek Inform Infostore
- Dearn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation