



NSAI
Standards

Standard Recommendation
S.R. CEN/TS 15912:2012

Durability of reaction to fire performance - Classes of fire-retardant treated wood- based product in interior and exterior end use applications

S.R. CEN/TS 15912:2012

Incorporating amendments/corrigenda/National Annexes issued since publication:

The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:

I.S. xxx: Irish Standard – national specification based on the consensus of an expert panel and subject to public consultation.

S.R. xxx: Standard Recommendation - recommendation based on the consensus of an expert panel and subject to public consultation.

SWIFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.

This document replaces:

This document is based on:
CEN/TS 15912:2012

Published:
30 April, 2012

This document was published
under the authority of the NSAI
and comes into effect on:
30 April, 2012

ICS number:
71.100.50

NSAI
1 Swift Square,
Northwood, Santry
Dublin 9

T +353 1 807 3800
F +353 1 807 3838
E standards@nsai.ie
W NSAI.ie

Sales:
T +353 1 857 6730
F +353 1 857 6729
W standards.ie

Údarás um Chaighdeáin Náisiúnta na hÉireann

ICS 71.100.50

English Version

Durability of reaction to fire performance - Classes of fire-retardant treated wood-based product in interior and exterior end use applications

Durabilité des performances de réaction au feu -
Classement des produits à base de bois ignifugés pour
utilisation finale en intérieur et en extérieur

Dauerhaftigkeit des Verhaltens bei Brandeinwirkung -
Klassen der mit Feuerschutzmitteln behandelten
Holzprodukte für Anwendungen im Innen- und
Außenbereich

This Technical Specification (CEN/TS) was approved by CEN on 14 February 2012 for provisional application.

The period of validity of this CEN/TS is limited initially to three years. After two years the members of CEN will be requested to submit their comments, particularly on the question whether the CEN/TS can be converted into a European Standard.

CEN members are required to announce the existence of this CEN/TS in the same way as for an EN and to make the CEN/TS available promptly at national level in an appropriate form. It is permissible to keep conflicting national standards in force (in parallel to the CEN/TS) until the final decision about the possible conversion of the CEN/TS into an EN is reached.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

Page

Foreword.....	4
Introduction	5
1 Scope	6
2 Normative references	6
3 Terms and definitions	6
4 Symbols	7
5 Requirements	7
5.1 Wood-based products and non-fire-retardant coating systems.....	7
5.2 Reaction to fire performance	8
5.2.1 Initial classification for reaction to fire.....	8
5.2.2 Reaction to fire performance before and after accelerated or natural weathering.....	8
5.3 Durability of reaction to fire performance	9
5.3.1 General.....	9
5.3.2 DRF Class ST	9
5.3.3 DRF Class INT1	9
5.3.4 DRF Class INT2	9
5.3.5 DRF Class EXT	9
6 Practices to use the DRF classification system	11
7 Classification report	11
Annex A (informative) Test methods.....	13
A.1 Hygroscopic properties of fire-retardant treated wood-based products including those with fire-retardant coatings	13
A.1.1 General.....	13
A.1.2 Field of application	13
A.1.3 Sampling, sample handling and preparation	14
A.1.4 Test method.....	15
A.2 Accelerated weathering of fire-retardant treated wood for fire testing.....	17
A.2.1 General.....	17
A.2.2 Field of application	18
A.2.3 Sampling, sample handling and preparation	18
A.2.4 Test method.....	19
A.3 Building materials and components in the vertical position: Exposure to accelerated climate strains.....	21
A.3.1 General.....	21
A.3.2 Field of application	21
A.3.3 Sampling	21
A.3.4 Test method.....	22
Annex B (informative) Example of classification report.....	26
B.1 Classification report: Durability classes of reaction to fire performance of fire-retardant wood-based products in interior and exterior end use applications according to CEN/TS 15912	26
B.1.1 Product	26
B.1.2 Product specification	26
B.1.3 Requirements	27
B.1.4 Evaluation documents	27
B.1.5 Durability of reaction to fire performance (DRF) Class	28
B.1.6 Applicability of DRF Class	28

B.1.7 Service life.....	29
Bibliography.....	30

Foreword

This document (CEN/TS 15912:2012) has been prepared by Technical Committee CEN/TC 175 “Round and sawn timber”, the secretariat of which is held by AFNOR.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

According to the CEN/CENELEC Internal Regulations, the national standards organisations of the following countries are bound to announce this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Introduction

Fire-retardant treatments may considerably improve the reaction to fire properties of wood and wood-based products and these may result in wood having the highest fire-resisting characteristics achievable with any combustible product. However, the reaction to fire performance may be reduced by exposure to wet and/or humid conditions [1] and the ability of treatments to continue to perform even when exposed to these conditions needs to be demonstrated.

Two aspects of fire durability of the fire-retardant treatment of wood-based products need to be considered. One is the risk for high moisture content and migration of the fire-retardant chemicals within the wood product and salt crystallisation on the product surface. These hygroscopic properties of the treated wood-based product can be evaluated by exposure to high relative humidity.

The other aspect is the risk for decreased fire performance due to loss of the fire-retardant chemicals by leaching in exterior applications, e.g. facade claddings. Maintained fire performance after weathering needs to be verified.

The Technical Specification is based on a Nordtest standard [15] and on experience from North America [7] [12].

1 Scope

This European Technical Specification describes the characteristics which fire-retardant treated wood products should exhibit so that their fire-retardant properties persist undiminished throughout the desired service life in the anticipated conditions of use.

The Technical Specification prescribes the classification requirements for the durability of the reaction to fire performance of fire-retardant treated wood-based products to be used in interior and exterior end use conditions. The products initially need to meet required reaction to fire classification. For interior and exterior use, limited hygroscopicity needs to be verified. In addition, products for exterior use need to meet the minimum durability of reaction to fire performance requirements specific to the end use.

The requirements are applicable for fire-retardant treated (applied by penetrating and superficial processes or with film forming or intumescent fire-retardant coatings) solid wood and wood-based products and wood-based products in which the fire-retardant is incorporated during manufacture. The fire-retardant treated products may be coated with an ordinary paint.

Mechanical properties and biological durability of fire-retardant treated wood products are not covered by this European Technical Specification.

Paints, coatings and varnishes intended to improve the reaction to fire performance of a construction product when incorporated in the works, i.e. a building, are covered by ETAG 028 [19].

This Technical Specification may be used as a basis for an approval system.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 927-3, *Paints and varnishes — Coating materials and coating systems for exterior wood — Part 3: Natural weathering test*

EN 13238, *Reaction to fire tests for building products — Conditioning procedures and general rules for selection of substrates*

EN 13823, *Reaction to fire tests for building products — Building products excluding floorings exposed to the thermal attack by a single burning item*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

durability of reaction to fire performance

DRF

four classes for the Durability of Reaction to Fire performance are defined:

- **DRF Class ST** for short term use (e.g. less than one year); no durability performance shall be verified;
- **DRF Class INT1** for permanent use in interior applications, service class 1 (e.g. wall and ceiling products);

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

-
- Looking for additional Standards? Visit Intertek Inform Infostore
 - Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation
-