



NSAI
Standards

Irish Standard Recommendation
S.R. CLC/TS 50131-2-8:2012&IS1:2014

Alarm systems - Intrusion and hold-up systems -- Part 2-8: Intrusion detectors - Shock detectors

S.R. CLC/TS 50131-2-8:2012&IS1:2014

Incorporating amendments/corrigenda/National Annexes issued since publication:

CLC/TS 50131-2-8:2012/IS1:2014

The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:

I.S. xxx: Irish Standard — national specification based on the consensus of an expert panel and subject to public consultation.

S.R. xxx: Standard Recommendation — recommendation based on the consensus of an expert panel and subject to public consultation.

SWiFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.

This document replaces/revises/consolidates the NSAI adoption of the document(s) indicated on the CEN/CENELEC cover/Foreword and the following National document(s):

NOTE: The date of any NSAI previous adoption may not match the date of its original CEN/CENELEC document.

This document is based on:

CLC/TS 50131-2-8:2012

Published:

2012-04-13

This document was published under the authority of the NSAI and comes into effect on:

2014-03-11

ICS number:

13.320

NOTE: If blank see CEN/CENELEC cover page

NSAI
1 Swift Square,
Northwood, Santry
Dublin 9

T +353 1 807 3800
F +353 1 807 3838
E standards@nsai.ie
W NSAI.ie

Sales:
T +353 1 857 6730
F +353 1 857 6729
W standards.ie

Údarás um Chaighdeáin Náisiúnta na hÉireann

INTERPRETATION SHEET

CLC/TS 50131-2-8/IS1

FEUILLE D'INTERPRETATION

INTERPRETATIONSBLATT

February 2014

ICS 13.320

English version

**Alarm systems -
Intrusion and hold-up systems -
Part 2-8: Intrusion detectors -
Shock detectors**

Systemes d'alarme -
Systemes d'alarme contre l'intrusion et les
hold-up -
Partie 2-8: Detecteurs d'intrusion -
Detecteurs de chocs

Alarmanlagen -
Einbruchmeldeanlagen -
Teil 2-8: Anforderungen an
Erschütterungsmelder

This Technical Specification was approved by CENELEC on 2013-12-23.

CENELEC members are required to announce the existence of this TS in the same way as for an EN and to make the TS available promptly at national level in an appropriate form. It is permissible to keep conflicting national standards in force.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B - 1000 Brussels

CLC/TS 50131-2-8:2012/IS1:2014 (E)

Contents	Page
Foreword	3
Clause:	4
Question:	4
Interpretation:	4
Validity:	4

Foreword

This Interpretation Sheet to the European Standard CLC/TS 50131-2-8:2012 was prepared by CLC/TC 79 "Alarm systems".

CLC/TS 50131-2-8:2012/IS1:2014 (E)

Text of IS1 to EN 50131-2-8:2012

Clause:

Annex B and Figure B.1

Question:

Would it be allowed for test purposes (for test houses and manufacturers) to use the NeoDym magnet listed below instead of the AlNiCo version described in Annex B and Figure B.1 for reproducible tests ?

Interpretation:

Yes, because this will allow stable and reproducible test results, which is not guaranteed while using the AlNiCo magnet due to the nature of the magnet material. Furthermore, the test magnet described below allows a high-level degree of backward compatibility for already tested products, while it gives the stability required.

Therefore, when the NeoDym magnet is used for test purposes (for test houses and manufacturers), the text below may be used in place of Annex B.

Validity:

This interpretation remains valid until an amendment or updated standard dealing with this issue is published by CENELEC.

Annex B (normative)

Dimensions and requirements of the standardised test magnets

B.1 Normative references

The interference test magnets shall comprise a magnet identical to the corresponding magnet supplied with the detector and one of the following specified independent test magnets according to whether the detector is surface or flush mounted.

The following standards will form the base for the selection of the independent test magnet:

EN 60404-5, *Magnetic materials – Part 5: Permanent magnet (magnetically hard) materials – Methods of measurement of magnetic properties (IEC 60404-5)*

EN 60404-14, *Magnetic materials – Part 14: Methods of measurement of the magnetic dipole moment of a ferromagnetic material specimen by the withdrawal or rotation method (IEC 60404-14)*

IEC 60404-8-1, *Magnetic materials – Part 8-1: Specifications for individual materials – Magnetically hard materials*

B.2 Requirements

The field strength of the magnet determined by the magnetic material, by remanence (B_r) in mT and the product of energy $(BH)_{\max}$ in kJ/m^3 , which are material dependent as the values describe the full saturation of that material should be measured before any calibration took place.

The field strength of the test magnet needs to be adjusted at the polarization of the working point in mT as defined.


The relevant value, dimensions and measurement point for the test magnet can be found in the following drawings and tables. For calculations, measurements and calibration of the test magnets, the norms cited above shall be used.

The independent test magnet for Test Magnet Type 1 is described in Figure B.1.

To get the magnets in question adjusted to the proper values and calibrated (e.g. polarization in working point), it is strongly suggested to perform adjustments of the magnetic values for ordered magnets performed by an accredited test house for magnetic fields. One potential source could be the following:

MAGNET-PHYSIK
Dr. Steingroever GmbH
Emil-Hoffmann-Strasse 3
50966 Cologne, Germany
www.magnet-physik.de

CLC/TS 50131-2-8:2012/IS1:2014 (E)



Key

- 1 North pole
- 2 South pole
- 3 North pole

Material	NdFeB N40 (REFeB 310/130 - Code number R5-1-11)
Remanence B_r min	1 275 mT \pm 2 %
Product of energy $(BH)_{max}$	310 kJ/m ³ \pm 3 %
Polarization of working point	0,835 T \pm 2 %

Figure B.1 – Magnet Type 1

TECHNICAL SPECIFICATION
SPÉCIFICATION TECHNIQUE
TECHNISCHE SPEZIFIKATION

CLC/TS 50131-2-8

April 2012

ICS 13.320

English version

**Alarm systems -
Intrusion and hold-up systems -
Part 2-8: Intrusion detectors -
Shock detectors**

Systemes d'alarme -
Systemes d'alarme contre l'intrusion et les
hold-up -
Partie 2-8: Détecteurs d'intrusion -
Détecteurs de chocs

Alarmanlagen -
Einbruchmeldeanlagen -
Teil 2-8: Anforderungen an
Erschütterungsmelder

This Technical Specification was approved by CENELEC on 2012-01-23.

CENELEC members are required to announce the existence of this TS in the same way as for an EN and to make the TS available promptly at national level in an appropriate form. It is permissible to keep conflicting national standards in force.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Management Centre: Avenue Marnix 17, B - 1000 Brussels

Contents

	Page
Foreword	4
Introduction	5
1 Scope	6
2 Normative references	6
3 Terms, definitions and abbreviations	6
3.1 Terms and definitions	7
3.2 Abbreviations	8
4 Functional requirements	8
4.1 General	8
4.2 Event Processing	8
4.3 Detection	10
4.3.1 Detection performance	10
4.3.2 Indication of detection	10
4.4 Immunity to false alarm sources	11
4.4.1 General	11
4.4.2 Immunity to Small objects hitting a framed window	11
4.4.3 Immunity to Hard objects hitting a framed window	11
4.4.4 Immunity to Static pressure	11
4.4.5 Immunity to Dynamic pressure	11
4.4.6 Standard Immunity Test	11
4.5 Operational requirements	11
4.5.1 Time interval between intrusion signals or messages	11
4.5.2 Switch on delay	12
4.5.3 Self tests	12
4.6 Tamper security	12
4.6.1 General	12
4.6.2 Resistance to and detection of unauthorised access to components and means of adjustment	13
4.6.3 Detection of removal from the mounting surface	13
4.6.4 Resistance to magnetic field interference	13
4.6.5 Detection of masking	13
4.7 Electrical requirements	14
4.7.1 General	14
4.7.2 Shock detectors current consumption	14
4.7.3 Slow input voltage change and voltage range limits	14
4.7.4 Input voltage ripple	14
4.7.5 Input voltage step change	14
4.8 Environmental classification and conditions	14
4.8.1 Environmental classification	14
4.8.2 Immunity to environmental conditions	15
5 Marking, identification and documentation	15
5.1 Marking and/or identification	15
5.2 Documentation	15
6 Testing	15
6.1 General	15
6.2 General test conditions	16
6.2.1 Standard conditions for testing	16
6.2.2 General detection testing environment and procedures	16
6.3 Basic Detection Test	16
6.3.1 General	16
6.3.2 Basic Detection Test Method	16
6.4 Performance tests	17
6.4.1 General	17
6.4.2 Verification of detection performance	17
6.5 Switch-on delay, time interval between signals and indication of detection	18
6.6 Self tests	19
6.7 Immunity to incorrect operation	19

6.7.1	General	19
6.7.2	Immunity to Small objects hitting the glass	19
6.7.3	Immunity to Hard objects hitting a framed window.....	20
6.7.4	Immunity to Static pressure	20
6.7.5	Immunity to Dynamic pressure	21
6.7.6	Standard Immunity Test	21
6.8	Tamper security.....	22
6.8.1	General	22
6.8.2	Resistance to and detection of unauthorised access to the inside of the shock detector through covers and existing holes	22
6.8.3	Detection of removal from the mounting surface.....	22
6.8.4	Resistance to magnetic field interference	22
6.8.5	Detection of shock detector masking	23
6.9	Electrical tests.....	23
6.9.1	General	23
6.9.2	Shock detector current consumption	23
6.9.3	Slow input voltage change and input voltage range limits	24
6.9.4	Input voltage ripple	24
6.9.5	Input voltage step change	25
6.9.6	Total loss of power supply	25
6.10	Environmental classification and conditions.....	25
6.11	Marking, identification and documentation	27
6.11.1	Marking and/or identification.....	27
6.11.2	Documentation	27
Annex A (normative)	Standard test material	28
Annex B (normative)	Dimensions and requirements of the standardised Test Magnets.....	29
Annex C (normative)	General Testing Matrix	32
Annex D (normative)	Standard immunity glass pane.....	34
Annex E (normative)	Spring operated Hammer	35
Annex F (informative)	Example list of small tools	36
Annex G (normative)	Minimum performance requirements gross and shock integration attack tests.....	37
Annex H (normative)	Immunity test: Small objects hit sensitivity	38
Annex I (normative)	Immunity test: Hard objects hit sensitivity.....	39
Annex J (normative)	Immunity test: Static pressure sensitivity	40
Annex K (normative)	Immunity test: Dynamic pressure sensitivity	41
Bibliography	42

Foreword

This document (CLC/TS 50131-2-8:2012) has been prepared by CLC/TC 79 "Alarm systems".

This document was circulated for voting in accordance with the Internal Regulations, Part 2, Subclause 11.3.3.3.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

Introduction

This document is a Technical Specification for shock detectors used as part of intrusion alarm systems installed in buildings. It includes four security grades and four environmental classes.

The purpose of a shock detector is to detect the shock or series of shocks due to a forcible attack through a physical barrier (for example doors or windows) and provide the necessary range of signals or messages to be used by the rest of the intrusion and hold-up alarm system.

The number and scope of these signals or messages will be more comprehensive for systems that are specified at the higher grades.

This Technical Specification is only concerned with the requirements and tests for the shock detectors.

1 Scope

This Technical Specification is for shock detectors installed in buildings to detect the shock or series of shocks due to a forcible attack through a physical barrier (for example doors or windows).

It provides for security Grades 1-4 (see EN 50131-1), specific or non specific wired or wire-free detectors and uses Environmental Classes i-iv (see EN 50130-5).

This Technical Specification does not include requirements for detectors intended to protect for example vaults and safes from penetration attacks from e.g. drilling, cutting or thermal lance.

This Technical Specification does not include requirements for shock detectors intended for use outdoors.

A detector shall fulfil all the requirements of the specified grade.

Functions additional to the mandatory functions specified in this Technical Specification may be included in the detector, providing they do not adversely influence the correct operation of the mandatory functions.

This Technical Specification does not apply to system interconnections.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 50130-4:2011, *Alarm systems — Part 4: Electromagnetic compatibility — Product family standard: Immunity requirements for components of fire, intruder and social alarm systems*

EN 50130-5:2011, *Alarm systems — Part 5: Environmental test methods*

EN 50131-1, *Alarm Systems — Intrusion systems and hold-up systems — Part 1: System requirements*

EN 50131-6, *Alarm systems — Intrusion systems and hold-up systems — Part 6: Power supplies*

EN 60068-1:1994, *Environmental testing — Part 1: General and guidance (IEC 60068-1:1988 + A1:1992 + corrigendum Oct. 1988)*

EN 60068-2-75:1997, *Environmental testing — Part 2-75: Tests — Test Eh: Hammer tests (IEC 60068-2-75:1997)*

IEC 68-2-52:1984, *Environmental testing — Part 2: Tests — Test Kb: Salt mist, cyclic (sodium, chloride solution)*

3 Terms, definitions and abbreviations

For the purposes of this document, the terms, definitions and abbreviations given in EN 50131-1 and the following apply.

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

-
- [Looking for additional Standards? Visit Intertek Inform Infostore](#)
 - [Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation](#)
-