



**NSAI**  
Standards

Irish Standard Recommendation  
S.R. CLC/TS 50238-2:2015

# Railway applications - Compatibility between rolling stock and train detection systems - Part 2: Compatibility with track circuits

**S.R. CLC/TS 50238-2:2015**

*Incorporating amendments/corrigenda/National Annexes issued since publication:*

The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:

I.S. xxx: Irish Standard — national specification based on the consensus of an expert panel and subject to public consultation.

S.R. xxx: Standard Recommendation — recommendation based on the consensus of an expert panel and subject to public consultation.

SWiFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.

*This document replaces/revises/consolidates the NSAI adoption of the document(s) indicated on the CEN/CENELEC cover/Foreword and the following National document(s):*

*NOTE: The date of any NSAI previous adoption may not match the date of its original CEN/CENELEC document.*

*This document is based on:*

CLC/TS 50238-2:2015

*Published:*

2015-05-22

*This document was published under the authority of the NSAI and comes into effect on:*

2015-06-09

ICS number:

29.280

45.060.10

NOTE: If blank see CEN/CENELEC cover page

NSAI  
1 Swift Square,  
Northwood, Santry  
Dublin 9

T +353 1 807 3800  
F +353 1 807 3838  
E standards@nsai.ie  
W NSAI.ie

Sales:  
T +353 1 857 6730  
F +353 1 857 6729  
W standards.ie

Údarás um Chaighdeáin Náisiúnta na hÉireann

TECHNICAL SPECIFICATION  
SPÉCIFICATION TECHNIQUE  
TECHNISCHE SPEZIFIKATION

**CLC/TS 50238-2**

May 2015

ICS 29.280; 45.060.10

Supersedes CLC/TS 50238-2:2010

English Version

**Railway applications - Compatibility between rolling stock and  
train detection systems - Part 2: Compatibility with track circuits**

Applications ferroviaires - Compatibilité entre le matériel  
roulant et les systèmes de détection des trains - Partie 2 -  
Compatibilité avec les circuits de voie

Bahnanwendungen - Kompatibilität zwischen Fahrzeugen  
und Gleisfreimeldesystemen - Teil 2: Kompatibilität mit  
Gleisstromkreisen

This Technical Specification was approved by CENELEC on 2015-04-20.

CENELEC members are required to announce the existence of this TS in the same way as for an EN and to make the TS available promptly at national level in an appropriate form. It is permissible to keep conflicting national standards in force.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization  
Comité Européen de Normalisation Electrotechnique  
Europäisches Komitee für Elektrotechnische Normung

**CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels**

## Contents

Foreword .....	5
Introduction .....	6
1 Scope .....	7
2 Normative references .....	7
3 Terms, definitions and abbreviations.....	8
3.1 Terms and definitions .....	8
3.2 Abbreviations .....	9
4 General aspects of interference current limits for RST.....	10
4.1 Derivation of interference current limits for RST.....	10
4.2 Application of Interference current limits to RST design .....	11
4.3 System definition .....	11
Annex A (normative) Interference current limits for RST .....	14
A.1 Definitions .....	14
A.2 Preferred track circuits for DC traction.....	14
A.3 Preferred track circuits for RST for 16,7 Hz traction .....	15
A.4 Preferred track circuits for RST for 50 Hz traction .....	15
A.5 UGSK3 .....	16
A.6 UGSK95 .....	16
A.7 FTGS 46 / FTGS 917/TCM100 .....	16
A.8 GRS.....	17
A.9 Jade .....	17
A.10 Coded track circuits for DC traction.....	18
A.11 Digicode .....	18
A.12 CoRTo.....	18
A.13 CBDAC.....	19
A.14 Preferred track circuit in Czech Republic.....	19
A.15 All kind of UM71 equipped with RENUM receptor and UC 9500.....	20
A.16 DC track circuits in UK .....	20
A.17 EBI Track 200 (TI21) .....	21
A.18 EBI Track 400 .....	21
A.19 FS3000 .....	22
A.20 FS2000 / FS 2500 / FS 2550 / FS 5000 .....	23
A.21 Track circuits of 95 Hz and 105 Hz in Norway.....	23
A.22 JRK 10470 .....	24
Annex B (normative) Rolling Stock Interference Evaluation methods.....	25
B.1 General .....	25
B.2 Selected evaluation method.....	25
B.3 Derivation of the interference current limits for RST .....	26
B.4 Criteria for compatibility .....	27
B.4.1 Location .....	27
B.4.2 Criteria 27	

<b>B.4.3 Safety and availability</b> .....	<b>27</b>
<b>B.5 Defined interference current limits for RST: for use under interoperability regulation</b> .....	<b>27</b>
<b>B.6 Test specifications for RST interference measurements</b> .....	<b>27</b>
<b>B.6.1 General</b> .....	<b>27</b>
<b>B.6.2 Purpose of compatibility tests</b> .....	<b>28</b>
<b>B.7 Test equipment requirements (hardware)</b> .....	<b>31</b>
<b>B.8 Train interference analysis and evaluation methods</b> .....	<b>31</b>
<b>B.8.1 Evaluation method</b> .....	<b>31</b>
<b>B.8.2 Summation rules</b> .....	<b>32</b>
<b>B.9 Requirements for on-train interference monitoring and control</b> .....	<b>33</b>
<b>B.10 Documentation</b> .....	<b>34</b>
<b>Annex C (informative) Infrastructure data</b> .....	<b>35</b>
<b>C.1 Supply frequency</b> .....	<b>35</b>
<b>C.2 Infrastructure characterization</b> .....	<b>35</b>
<b>C.3 Power supply impedance</b> .....	<b>36</b>
<b>C.4 Approximate calculation of the lowest power supply resonance frequency</b> .....	<b>36</b>
<b>C.5 Simplified method to handle resonance effects with roof cables</b> .....	<b>37</b>
<b>C.6 Return current transfer function</b> .....	<b>39</b>
<b>Annex D (informative) Typical voltage resonance graphs</b> .....	<b>40</b>
<b>D.1 General</b> .....	<b>40</b>
<b>D.2 Interface voltage/current measurement</b> .....	<b>40</b>
<b>D.3 Voltage resonance graphs for 15 kV 16,7 Hz network</b> .....	<b>40</b>
<b>D.4 Voltage resonance graphs for 25 kV, 50 Hz network</b> .....	<b>41</b>
<b>D.5 Voltage resonance graphs for 1 500 V DC network</b> .....	<b>41</b>
<b>D.6 Voltage resonance graphs for 3 000 V DC network</b> .....	<b>42</b>
<b>Bibliography</b> .....	<b>43</b>

## Figures

<b>Figure 1 — Examples of IUs</b> .....	<b>9</b>
<b>Figure 2 — System configuration considered for interference</b> .....	<b>12</b>
<b>Figure B.1 — Time domain method</b> .....	<b>26</b>
<b>Figure B.2 — Superposition factors</b> .....	<b>33</b>
<b>Figure C.1 — Infrastructure characterization</b> .....	<b>35</b>
<b>Figure C.2 — Power supply admittance</b> .....	<b>36</b>
<b>Figure C.3 — Resonance effects for various RST positions</b> .....	<b>38</b>
<b>Figure C.4 — Resonance effects for various RST input capacitance</b> .....	<b>39</b>
<b>Figure D.1 — Voltage resonance graph for 15 kV 16,7 Hz network</b> .....	<b>41</b>
<b>Figure D.2 — Voltage resonance graphs for 25 kV 50 Hz network</b> .....	<b>41</b>
<b>Figure D.3 — Voltage resonance graphs for 1 500 V DC network</b> .....	<b>42</b>
<b>Figure D.4 — Impedance graphs for 3 000 V DC network</b> .....	<b>42</b>

## Tables

<b>Table A.1 — UGSK3 .....</b>	<b>16</b>
<b>Table A.2 — UGSK95 .....</b>	<b>16</b>
<b>Table A.3 — FTGS/TCM100 .....</b>	<b>16</b>
<b>Table A.4 — GRS .....</b>	<b>17</b>
<b>Table A.5 — GRS - limits due to rectifying traction supply .....</b>	<b>17</b>
<b>Table A.6 — Jade 25 kV, 50 Hz lines .....</b>	<b>17</b>
<b>Table A.7 — Jade DC lines .....</b>	<b>18</b>
<b>Table A.8 — Limits for BACC and CDB 83,3 Hz .....</b>	<b>18</b>
<b>Table A.9 — Digicode.....</b>	<b>18</b>
<b>Table A.10 — CoRTo.....</b>	<b>18</b>
<b>Table A.11 — CBDAC.....</b>	<b>19</b>
<b>Table A.12 — 50 Hz AC and DC Traction.....</b>	<b>19</b>
<b>Table A.13 — UM71 C, UM71 CB, UM71C TVM and UC9500 .....</b>	<b>20</b>
<b>Table A.14 — DC track circuits in UK.....</b>	<b>20</b>
<b>Table A.15 — EBI Track 200 (TI-21) Double Rail Limit for in-band frequencies — AC traction only .....</b>	<b>21</b>
<b>Table A.16 — EBI Track 200 (TI-21) Double Rail Limit for in-band frequencies — DC traction or non-electrified lines .....</b>	<b>21</b>
<b>Table A.17 — EBI Track 400 Open Line Frequency Double Rail Track Circuit Limit for in-band frequencies .....</b>	<b>21</b>
<b>Table A.18 — EBI Track 400 Open Line Frequency Double Rail Track Circuit Limit for out of band frequencies.....</b>	<b>22</b>
<b>Table A.19 — EBI Track 400 Station Area Frequency Double Rail Track Circuit Limit.....</b>	<b>22</b>
<b>Table A.20 — FS3000 3 kV, DC lines .....</b>	<b>22</b>
<b>Table A.21 — FS3000 25 kV, 50 Hz lines.....</b>	<b>23</b>
<b>Table A.22 — FS2000 / FS 2500 / FS 2550 / FS 5000 3 kV, DC lines.....</b>	<b>23</b>
<b>Table A.23 — Track circuits of 95 Hz and 105 Hz in Norway .....</b>	<b>23</b>
<b>Table A.24 — JRK 10470 .....</b>	<b>24</b>
<b>Table B.1 — Reduction factors for capacitive input impedance .....</b>	<b>30</b>
<b>Table B.2 — Summation categories.....</b>	<b>32</b>
<b>Table B.3 — K factor values .....</b>	<b>33</b>
<b>Table C.1 — Supply frequency .....</b>	<b>35</b>
<b>Table C.2 — Capacitance parameters for electrified lines.....</b>	<b>37</b>
<b>Table C.3 — No-load supply voltage levels .....</b>	<b>37</b>
<b>Table D.1 — Measurement parameters .....</b>	<b>40</b>
<b>Table D.2 — Measurement frequencies.....</b>	<b>40</b>

## Foreword

This document (CLC/TS 50238-2:2015) has been prepared by CLC/SC 9XA "Communication, signalling and processing systems" of Technical Committee CLC/TC 9X, "Electrical and electronic applications for railways".

This document supersedes CLC/TS 50238-2:2010.

CLC/TS 50238-2:2015 includes the following significant technical changes with respect to CLC/TS 50238-2:2010:

- The interference current limits for RST have been updated in the normative Annex A.
- The measurement and evaluation methods for verifying conformity of rolling stock to the limits for interference current emissions have been moved to the new normative Annex B.

This Technical Specification is intended to become Part 2 of the EN 50238 series published under the title *Railway applications — Compatibility between rolling stock and train detection systems*. The series consists of:

- *Part 1: General*<sup>1)</sup>;
- *Part 2: Compatibility with track circuits* [this document];
- *Part 3: Compatibility with axle counters*.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

---

---

1) The existing EN 50238:2003 was renumbered EN 50238-1 when the voting procedure on Parts 2 and 3 was closed.

## **Introduction**

This Technical Specification is being developed to permit compliance with the Interoperability Directives (High Speed and Conventional).

This Part 2 of the series defines:

- a set of interference current limits for rolling stock based on defined track circuits,
- measurement and evaluation methods to verify rolling stock interference current emissions and demonstrate compatibility with the track circuits;
- traceability of compatibility requirements (types of track circuit and associated limits).



## 1 Scope

This Technical Specification defines, for the purpose of ensuring compatibility between rolling stock and track circuits, the limits for interference current emissions from rolling stock. The measurement and evaluation methods for verifying conformity of rolling stock to these limits are presented in a dedicated annex.

The interference limits are only applicable to interoperable rolling stock which is intended to run on lines exclusively equipped with preferred track circuits listed in this Technical Specification. National Notified Technical Rules are still to be used in all cases, where the line over which the rolling stock is intended to run is equipped with any type of older version or non-preferred track circuits that are not listed in this Technical Specification. However, the rolling stock test methodology (infrastructure conditions, test configurations, operational conditions, etc.) presented in this Technical Specification is also applicable to establish compatibility with non-preferred track circuits.

This Technical Specification gives guidance on the derivation of interference current limits specified for rolling stock and defines measurement methods and evaluation criteria in a dedicated annex.

This Technical Specification defines:

- a) a set of interference current limits for RST (Rolling Stock) applicable for each of the following types of traction system:
  - 1) DC (750 V, 1,5 kV and 3 kV);
  - 2) 16,7 Hz AC;
  - 3) 50 Hz AC;
- b) methodology for the demonstration of compatibility between rolling stock and track circuits;
- c) measurement method to verify interference current limits and evaluation criteria.

NOTE 1 The basic parameters of track circuits associated with the interference current limits for RST are not in the scope of this Technical Specification.

NOTE 2 Any phenomena linked to traction power supply and associated protection (over voltage, short-circuit current, under- and over-voltage if regenerative brakes are used) is part of the track circuit design and outside the scope of this Technical Specification.

## 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 50126 (all parts), *Railway applications — The specification and demonstration of Reliability, Availability, Maintainability and Safety (RAMS)*

EN 50128, *Railway applications — Communication, signalling and processing systems — Software for railway control and protection systems*

EN 50129, *Railway applications — Communication, signalling and processing systems — Safety related electronic systems for signalling*

EN 50238-1:2003, *Railway applications — Compatibility between rolling stock and train detection systems — Part 1: General*

CLC/TS 50238-3:2013, *Railway applications — Compatibility between rolling stock and train detection systems — Part 3: Compatibility with axle counters*

EN 50388, *Railway Applications — Power supply and rolling stock — Technical criteria for the coordination between power supply (substation) and rolling stock to achieve interoperability*

CLC/TR 50507, *Railway applications — Interference limits of existing track circuits used on European railways*

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

- 
- [Looking for additional Standards? Visit Intertek Inform Infostore](#)
  - [Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation](#)
-