

Irish Standard I.S. EN ISO 5167-5:2016

Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full -Part 5: Cone meters (ISO 5167-5:2016)

 $\ensuremath{\mathbb C}$ CEN 2016 $\hfill No copying without NSAI permission except as permitted by copyright law.$

I.S. EN ISO 5167-5:2016

Incorporating amendments/corrigenda/National Annexes issued since publication:

The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:

I.S. xxx: Irish Standard – national specification based on the consensus of an expert panel and subject to public consultation.

S.R. xxx: Standard Recommendation — recommendation based on the consensus of an expert panel and subject to public consultation.

SWIFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.

This document replaces/revises/consolidates the NSAI adoption of the document(s) indicated on the CEN/CENELEC cover/Foreword and the following National document(s):

NOTE: The date of any NSAI previous adoption may not match the date of its original CEN/CENELEC document.

This document is based on: EN ISO 5167-5:2016 *Published:* 2016-03-30

This document was published under the authority of the NSAI and comes into effect on:

2016-04-17

ICS number:

NOTE: If blank see CEN/CENELEC cover page

| NSAI | T +353 1 807 3800 | Sales: |
|-------------------|---------------------|-------------------|
| 1 Swift Square, | F +353 1 807 3838 | T +353 1 857 6730 |
| Northwood, Santry | E standards@nsai.ie | F +353 1 857 6729 |
| Dublin 9 | W NSAI.ie | W standards.ie |

Údarás um Chaighdeáin Náisiúnta na hÉireann

National Foreword

I.S. EN ISO 5167-5:2016 is the adopted Irish version of the European Document EN ISO 5167-5:2016, Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full - Part 5: Cone meters (ISO 5167-5:2016)

This document does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with this document does not of itself confer immunity from legal obligations.

In line with international standards practice the decimal point is shown as a comma (,) throughout this document.

This is a free page sample. Access the full version online.

This page is intentionally left blank

EUROPEAN STANDARD NORME EUROPÉENNE

EN ISO 5167-5

EUROPÄISCHE NORM

March 2016

ICS 17.120.10

English Version

Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full - Part 5: Cone meters (ISO 5167-5:2016)

Mesure de débit des fluides au moyen d'appareils déprimogènes insérés dans des conduites en charge de section circulaire - Partie 5: Cônes de mesure (ISO 5167-5:2016) Durchflussmessung von Fluiden mit Drosselgeräten in voll durchströmten Leitungen mit Kreisquerschnitt -Teil 5: Konus-Durchflussmesser (ISO 5167-5:2016)

This European Standard was approved by CEN on 4 February 2016.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

© 2016 CEN All rights of exploitation in any form and by any means reserved worldwide for CEN national Members.

Ref. No. EN ISO 5167-5:2016 E

This is a free page sample. Access the full version online. I.S. EN ISO 5167-5:2016

EN ISO 5167-5:2016 (E)

| Contents | Page |
|-------------------|------|
| European foreword | |

European foreword

This document (EN ISO 5167-5:2016) has been prepared by Technical Committee ISO/TC 30 "Measurement of fluid flow in closed conduits".

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by September 2016, and conflicting national standards shall be withdrawn at the latest by September 2016.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Endorsement notice

The text of ISO 5167-5:2016 has been approved by CEN as EN ISO 5167-5:2016 without any modification.

This is a free page sample. Access the full version online.

This page is intentionally left blank

INTERNATIONAL STANDARD

ISO 5167-5

First edition 2016-03-01

Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full —

Part 5: **Cone meters**

Mesure de débit des fluides au moyen d'appareils déprimogènes insérés dans des conduites en charge de section circulaire —

Partie 5: Cônes de mesure



Reference number ISO 5167-5:2016(E) ISO 5167-5:2016(E)



© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Ch. de Blandonnet 8 • CP 401 CH-1214 Vernier, Geneva, Switzerland Tel. +41 22 749 01 11 Fax +41 22 749 09 47 copyright@iso.org www.iso.org

Contents

| Page |
|------|
|------|

| Foreword | | iv |
|-------------------------------------|--|----------|
| Introduction | | v |
| 1 Scope | | 1 |
| 2 Normative refere | ences | |
| 3 Terms and defini | itions | 1 |
| A Principles of the | method of measurement and computation | 2 |
| F Concentration | method of measurement and computation | |
| 5 Cone meters | nlightion | 3 |
| 5.1 Field of ap | ano | |
| 5.2 General Sil | ape | |
| 5.5 Material al | annings | / ع |
| 5.5 Discharge | coefficient C | 0 |
| 5.5 Discharge | mits of use | 0 8 |
| 5.5.1 El | scharge coefficient of the cone meter | 0 8 |
| 5.6 Expansibil | ity (expansion) factor s | 0 9 |
| 5.0 Expansion | y of the discharge coefficient C | 9 |
| 5.8 Uncertaint | v of the expansibility (expansion) factor ε | 9 |
| 5.9 Pressure lo | SS | 9 |
| 6 Installation requ | irements | 10 |
| 6.1 General | in chiefts. | 10 |
| 6.2 Minimum | upstream and downstream straight lengths for installations between | 10 |
| various fitt | tings and the cone meter | |
| 6.2.1 Ge | eneral | |
| 6.2.2 Si | ngle 90° bend | 11 |
| 6.2.3 Tv | vo 90° bends in perpendicular planes | 11 |
| 6.2.4 Co | oncentric expander | 11 |
| 6.2.5 Pa | artially closed valves | 11 |
| 6.3 Additional | specific installation requirements for cone meters | 11 |
| 6.3.1 Ci | rcularity and cylindricality of the pipe | 11 |
| 6.3.2 Ro | oughness of the upstream and downstream pipe | 11 |
| 6.3.3 Pc | ositioning of a thermowell | |
| 7 Flow calibration | of cone meters | |
| 7.1 General | | |
| 7.2 Test facility | у | |
| 7.3 Meter inst | allation | |
| 7.4 Design of t | he test programme | |
| 7.5 Reporting | the calibration results | |
| 7.6 Uncertaint | y analysis of the calibration | |
| 7.6.1 Ge | eneral | 13 |
| 7.6.2 Ur | ncertainty of the test facility | 13 |
| 7.6.3 Ur | ncertainty of the cone meter | 13 |
| Annex A (informative) Ta | able of expansibility (expansion) factor | 14 |
| Bibliography | | |

This is a free page sample. Access the full version online I.S. EN ISO 5167-5:2016

ISO 5167-5:2016(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 30, *Measurement of fluid flow in closed conduits*, Subcommittee SC 2, *Pressure differential devices*.

The first edition of ISO 5167-5 is complementary to ISO 5167-1, ISO 5167-2, ISO 5167-3, and ISO 5167-4.

ISO 5167 consists of the following parts, under the general title *Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full:*

- Part 1: General principles and requirements
- Part 2: Orifice plates
- Part 3: Nozzles and Venturi nozzles
- Part 4: Venturi tubes
- Part 5: Cone meters

Introduction

This International Standard, divided into five parts, covers the geometry and method of use (installation and operating conditions) of orifice plates, nozzles, Venturi tubes, and cone meters when they are inserted in a conduit running full to determine the flow rate of the fluid in the conduit. It also gives necessary information for calculating the flow rate and its associated uncertainty.

This International Standard is applicable only to pressure differential devices in which the flow remains subsonic throughout the measuring section and where the fluid can be considered as single-phase, but it is not applicable to the measurement of pulsating flow. Furthermore, each of these devices can only be used within specified limits of pipe size and Reynolds number.

This International Standard deals with devices for which direct calibration experiments have been made sufficient in number, spread, and quality to enable coherent systems of application to be based on their results and coefficients to be given with certain predictable limits of uncertainty. However, for cone meters calibrated in accordance with <u>Clause 7</u>, a wider range of pipe size, β , and Reynolds number may be considered.

The devices introduced into the pipe are called "primary devices". The term primary device also includes the pressure tappings. All other instruments or devices required for the measurement are known as "secondary devices". This International Standard covers primary devices; secondary devices^{[1][5]} will be mentioned only occasionally.

This International Standard is divided into the following five parts:

- a) ISO 5167-1 gives general terms and definitions, symbols, principles, and requirements as well as methods of measurement and uncertainty that are to be used in conjunction with ISO 5167-1, ISO 5167-2, ISO 5167-3, ISO 5167-4, and ISO 5167-5.
- b) ISO 5167-2 specifies requirements for orifice plates, which can be used with corner pressure tappings, D and D/2 pressure tappings¹), and flange pressure tappings.
- c) ISO 5167-3 specifies requirements for ISA 1932 nozzles²⁾, long radius nozzles, and Venturi nozzles, which differ in shape and in the position of the pressure tappings.
- d) ISO 5167-4 specifies requirements for classical Venturi tubes³).
- e) This part of ISO 5167 specifies requirements for cone meters and includes a section on calibration.

Aspects of safety are not dealt with in ISO 5167 (all parts). It is the responsibility of the user to ensure that the system meets applicable safety regulations.

¹⁾ Orifice plates with 'vena contracta' pressure tappings are not considered in ISO 5167 (all parts).

²⁾ ISA is the abbreviation for the International Federation of the National Standardizing Associations, which was succeeded by ISO in 1946.

³⁾ In the USA, the classical Venturi tube is sometimes called the Herschel Venturi tube.

This is a free page sample. Access the full version online. I.S. EN ISO 5167-5:2016

Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full —

Part 5: **Cone meters**

1 Scope

This part of ISO 5167 specifies the geometry and method of use (installation and operating conditions) of cone meters when they are inserted in a conduit running full to determine the flow rate of the fluid flowing in the conduit.

As the uncertainty of an uncalibrated cone meter might be too high for a particular application, it might be deemed essential to calibrate the flow meter in accordance with <u>Clause 7</u>.

This part of ISO 5167 also provides background information for calculating the flow rate and is applicable in conjunction with the requirements given in ISO 5167-1.

This part of ISO 5167 is applicable only to cone meters in which the flow remains subsonic throughout the measuring section and where the fluid can be considered as single-phase. Uncalibrated cone meters can only be used within specified limits of pipe size, roughness, β , and Reynolds number. This part of ISO 5167 is not applicable to the measurement of pulsating flow. It does not cover the use of uncalibrated cone meters in pipes sized less than 50 mm or more than 500 mm, or where the pipe Reynolds numbers are below 8×10^4 or greater than $1,2 \times 10^7$.

A cone meter is a primary device which consists of a cone-shaped restriction held concentrically in the centre of the pipe with the nose of the cone upstream. The design of cone meter defined in this part of ISO 5167 has one or more upstream pressure tappings in the wall, and a downstream pressure tapping positioned in the back face of the cone with the connection to a differential pressure transmitter being a hole through the cone to the support bar, and then up through the support bar.

Alternative designs of cone meters are available; however, at the time of writing, there is insufficient data to fully characterize these devices, and therefore, these meters shall be calibrated in accordance with <u>Clause 7</u>.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 4006, Measurement of fluid flow in closed conduits — Vocabulary and symbols

ISO 5167-1:2003, Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full — Part 1: General principles and requirements

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 4006, ISO 5167-1, and the following apply.



This is a free preview. Purchase the entire publication at the link below:

Product Page

S Looking for additional Standards? Visit Intertek Inform Infostore

> Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation